

42" Free Standing Pedestal Maximize Your Advertising Real Estate



Front View



Back ISO View

The **AOD-4200** Series is a high performance 42" LCD display which rounds out our DSS Series with the ultimate in All Weather and Solar conditions.

This unit is built to take the heat with temperature ranges from -4 Deg F (-20 Deg C) to 122 Deg F (50 Deg C).

These units have an optical bonded front lens with IR, UVa and UVb Protection against heat and optical front loading. Optional High-Brighted Unit can achieve 1000 NITS.

This Unit allows you to put your Digital Signage where the people are "Outside"

The **AOD-4200** is an all Aluminum construction solution with a Standard Finish of Tan Gloss Coat and medium texture, but it can be customized to any color.



Features

Enclosure:

Monitor: NEMA 4X (Water / Dust Tight)

- All Aluminum Construction

Pedestal:

- Top Houses ECU and Bottom is NEMA 4 housing the electronics, power supply, CPU, & Audio amplifiers.

Easily mountable to any flat surface

Display:

- 42" Diagonal Active Matrix TFT LCD Displays
- Available for Landscape or Portrait Viewing
- 160° / 160° Viewing Angle
- HD @1366 x 768 & FHD @ 1920x1080
- Contrast Ratio 500:1
- Brightness 600 NITS (Optional 1000 NITS High Bright Available)
- On Screen Display (OSD) Monitor Controls

Video Inputs:

- DVI-D, HDMI and aRGB - Supports all Major Video Formats

Power:

- +24 VDC Operation (Power converter included 110 AC to 24 VDC)

Other Features / Options:

Environmental Control Unit (ECU) Options:

Cooling for up to 120 Deg F ambient temperature and heating for operations below 32 Deg F.

Please feel free to consult with a Sales Engineer for additional information or visit our web site.

