Digital Signage LCD Monitor

High Brightness Chassis Stand Alone LCD Digital Signage Advertising Player, 15" 4:3, 1024x768, 1000nits, 1080P Full HD Supported video code format: MPG, MOV, MKV, AVI, MP4, TP, TS, DAT, RM, RMVB, Supported image format: BMP, JPEG

(Model: TDD1500HBMP)



FEATURES:

- ★ 1080P Full HD Supported video code format:MPG, MOV, MKV, , AVI, MP4, TP, TS, DAT, RM, RMVB
- ★ Supported image format:BMP, JPEG
- ★ Supported audio code format: MP3
- ★ When the machine is power failure and reset, it can start to playback from the current record before 5 or 10 or 30 seconds
- ★ Free split screen:

Window mode

Landscape: supports one, two, three split screen, logo, rolling subtitle

- ★ Clock display: a clock IC, time information can be displayed.
- ★ Audio output: two-channel stereo audio output 2X2W, SNR 85dB.
- ★ Rolling subtitles: Play video advertising, while at the bottom of the screen display pre-set text messages.
- ★ Play mode: repeat the whole song, single repeat playing, sequential playing.
- ★ Remote Control: Support Infrared Remote Control.
- ★ Support OTG copy function.
- ★ Support upgrading the firmware from USB port .(fastest)
- ★ Program playing there are two models as follows:

Set the multiple segment play time

Play the designate file in the playtime

Date setting adjusts the time value displayed on display terminals

Display the time value on the screen or not

Timing power on/off

You can set power on/off time per day/week

Provides 5-time range for power on/off

_			_			4.5
1	<i>I</i> C 1	em	· Sr	ACI	ITICS	itions
٠,٠	<i>1</i> 31		JL	,	\cdots	เนษแร

Viewable Size Image	15" 4:3		
Active Dispaly Area(mm)	304.1x228.1		
Pixel Pitch(mm)	0.297x0.297		
Number of Pixels	1024x768		
Contrast Ratio	600/800		
Display Color	16.7M colors		
Brightness	350 CCFL/400 LED		
Viewing Angle(CR>=10)	75/75 60/50(CCFL), 80/80		
	65/80(LED)		
Response Time	8		
Dimensions	WxHxD 365x285x50 mm		
Weight	N.W/G.W 2100g/2800g		



