


32" Widescreen Front 6mm Aluminum LCD Panel Model: iAP-W3200



Display Benefits

- 32" widescreen LCD with high resolution 1366 x 768
- Rugged construction against external impact
- Standard with HDMI, DVI-D, VGA, S-Video, RCA, Audio & remote controller

Options

- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi-display control solution
- W32" Touchscreen: Capacitive, Resistive
- Protective toughened glass
- MIL-type or lockable connector
- TV - Analog

Standard I/O



Specifications:

LCD Panel	
Size (diagonal) :	32" Widescreen TFT
Max resolution :	1366 x 768
Brightness (cd/m2) :	450
Backlight :	CCFL
Colors :	16.7 M
Contrast ratio (typ) :	5000 : 1
Viewing angle (H/V) :	178° x 178°
Active area (mm) :	698 x 392
MTBF (hrs) :	50,000
Signal input :	HDMI / DVI-D / VGA / S-Video / RCA
Weight	
Net / Gross :	23 kgs (50.6 lbs) / 39 kgs (85.8 lbs)
Mounting :	Wall-mount / VESA mount

Environmental	
Operating :	0 to 50°C Degree
Storage :	-5 to 60°C Degree
Relative humidity :	5-90%, non-condensing
Shock :	10G acceleration (11 ms duration)
Vibration :	5-500Hz 1G RMS random vibration
Casing Color :	Black front panel (RAL 9005) Dark grey rear case (RAL 7037)
Regulatory :	
	FCC, CE
Power	
Input :	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption :	Max. 200 Watt, Standby 20 Watt
Dimensions	
Product :	802 x 75 x 496 mm / 31.6 x 3 x 19.5 inch
Packing :	980 x 270 x 650 mm / 38.6 x 10.6 x 25.6 inch

Mechanical Drawing

Diagrams (mm)

Front View

Side View

Rear View

