

# NEMA 4 / IP65 front protection

Rugged industrial monitors/Panel Mount LCD  
Monitor 15" w/ VGA input

Model: iNAP-1500



## Display Benefits

- 15" LCD with resolution 1024 x 768
- Rugged construction against external impact
- 6mm aluminum front bezel with protective glass


## Options

- S-Video + Composite ( BNC )
- DVI-D or Audio input
- 15" Touchscreen : Capacitive, Resistive
- 48V, 24V or 12VDC power
- TV - Analogo

### Basic I/O



### AV2.2 upgrade I/O



## Specifications:

LCD Panel	
Size (diagonal) :	15" TFT
Max resolution :	1024 x 768
Brightness (cd/m2) :	250
Backlight :	CCFL
Colors :	16.2 M
Contrast ratio (typ) :	700 : 1
Viewing angle (H/V) :	150° x 135°
Active area (mm) :	304 x 228
MTBF (hrs) :	30,000
Signal input :	VGA
Weight	
Net / Gross :	4.7 kgs ( 10.3 lbs ) / 7.3 kgs ( 16.1 lbs )
Mounting :	Universal mount / VESA mount

Environmental	
Operating :	0 to 50°C Degree
Storage :	-5 to 60°C Degree
Relative humidity :	5-90%, non-condensing
aShock :	10G acceleration ( 11 ms duration )
Vibration :	5-500Hz 1G RMS random vibration
Casing Color :	Black front panel ( RAL 9005 ) Dark grey rear case ( RAL 7037 )
Regulatory :	FCC, CE
Power	
Input :	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption :	Max. 40 Watt, Standby 5 Watt
Dimensions	
Product :	407 x 59.1 x 313.6 mm / 16 x 2.3 x 12.3 inch
Packing :	615 x 113 x 523 mm / 24.2 x 4.4 x 20.6 inch

## Mechanical Drawing

### Diagrams ( mm )

Front View

Side View

Rear View

