

NEMA 4 / IP65 front protection

Front NEMA4 / IP 65 LED display panel, Industrial Metal Housing Panel Mount (6mm aluminum front bezel display panel) Samsung Widescreen 21.5" Panel mount LCD display panel, 1920 x 1080, VGA, VGA + DVI-D + HDMI input

Model: iNAP-W2150




Display Benefits

- 21.5" widescreen LCD with Full HD 1080p resolution
- PIP & Picture by Picture viewing efficiency
- Green LED-backlit panel technology
- Rugged construction against external impact
- 6mm aluminum front bezel with protective glass


Options

- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi-display control solution
- F21" Touchscreen : Capacitive, Resistive
- S-Video + Composite (BNC) or Audio input
- MIL-type or lockable connector
- 48V, 24V or 12VDC power
- TV - Analog

Basic I/O



AV3.0 upgrade I/O with advanced features



Specifications:

LCD Panel	
Size (diagonal) :	21.5" Widescreen TFT
Max resolution :	1920 x 1080
Brightness (cd/m2) :	250
Backlight :	LED
Colors :	16.7 M
Contrast ratio (typ) :	1000 : 1
Viewing angle (H/V) :	170° x 160°
Active area (mm) :	477 x 268
MTBF (hrs) :	30,000
Signal input :	VGA, DVI-D and HDMI
Weight	
Net / Gross :	6.9 kgs (15.2 lbs) / 10 kgs (22 lbs)
Mounting :	Panel mount / VESA mount

Environmental	
Operating :	0 to 50°C Degree
Storage :	-5 to 60°C Degree
Relative humidity :	5-90%, non-condensing
aShock :	10G acceleration (11 ms duration)
Vibration :	5-500Hz 1G RMS random vibration
Casing Color :	Dark grey rear case (RAL 7037)
Regulatory :	FCC, CE
Power	
Input :	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption :	Max. 40 Watt, Standby 5 Watt
Dimensions	
Product :	577.8 x 59.1 x 369.3 mm / 22.7 x 2.3 x 14.5 inch
Packing :	659 x 117 x 640 mm / 25.9 x 4.6 x 25.2 inch

Mechanical Drawing

Diagrams (mm)

Front View

Side View

Rear View

