



24" Front NEMA4/IP65 LCD Panel

Model: iNAP-W2400X

iNAP-W2400X

NEMA 4 / IP65 front protection

Display Benefits




- 24" widescreen LCD with 1920 x 1200 native WUXGA Ultra high resolution
- Standard with HDMI, DVI-D, VGA, S-Video, RCA, Audio & remote controller
- PIP & Picture by Picture viewing efficiency
- 6mm aluminum front bezel with protective glass & water proof sealed gasket
- Rugged construction against external impact

Options

- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi-display control solution
- Resistive (single point touch)
- 48V or 24VDC power
- MIL-type or lockable connector
- TV - Analog



Basic I/O



Specification:

LCD Panel	
Diagonal size	24.1" Widescreen TFT
Max. Resolution	1920 x 1200
Brightness (cd/m2)	400
Backlight	CCFL
Colors	1.07 Billion, 10-bit
Contrast Ratio (typ)	1000 : 1
Viewing Angle (H/V)	178° x 178°
Active area (mm)	518 x 324
MTBF (hrs)	40,000
Signal input	HDMI / DVI-D / VGA / S-Video / RCA
Weight	
Net / Gross :	11.8 kgs (26 lbs) / 15.5 kgs (34.1 lbs)
Mounting	Panel mount / VESA mount
Environmental	
Operating	0 to 50°C Degree
Storage	-5 to 60°C Degree
Relative humidity	5-90%, non-condensing

Shock	10G acceleration (11 ms duration)
Vibration	5-500Hz 1G RMS random vibration
Casing Color	Black (RAL 9005)
Regulatory	FCC, CE, RoHS
Safety	FCC & CE certified
Environmental	RoHS2 & REACH compliant
Power	
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption	Max. 48 Watt, Standby 5 Watt
Dimensions	
Product	620.4 x 87.1 x 426 mm / 24.4 x 3.4 x 16.8 inch
Packing	701 x 138 x 685 mm / 27.6 x 5.4 x 27 inch

Diagram (mm):

