

SEMI INDUSTRIAL DISPLAY PC

10.1" 1280 x800, Semi Industrial Display with P-Cap Touch /
Ultra slim. Intel Atom Z3735F 1.33GHz CPU/ 2G DDR3L/32GB eMMC/
LAN/2USB/WIFI/ 19V Adapter, Android 5.1 & UK power cord



Model: VPCW1040-S-AO

Features:

- Onboard Intel Atom Z3735F 1.33GHz Processor
- Onboard 2GB DDR3L Memory
- Onboard 32GB eMMC
- Projective Capacitive Multi-Touch
- IP65 Front Panel
- Membrane Power Button
- Onboard WIFI IEEE802.11 b/g/n

Specifications:

Processor	Intel Atom Z3735F 1.33GHz Processor
System Memory	Onboard 2GB DDR3L
I/O Chip	ENE D3737LU
Storage	
Storage	Onboard 32GB eMMC
I/O	
USB	2 x USB 2.0
Antenna	1 x Internal Antenna
HDMI	1 X HDMI Output
Display	
Chipset	Intel Gen7 HD Graphic
Resolution	HDMI: Max. Resolution 1920 x 1080 @ 60 Hz
Audio	
Chipset	Realtek ALC5645-CGT
Audio Interface	Line-Out
Speaker Output	2 x 1W (Optional)
Ethernet	
Chipset	Microchip LAN9512 10/100 Ethernet
Ethernet Interface	1 x RJ45
Mechanical & Environmental	
Power Type	ATX
Operating Temp	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-10°C ~ 60°C (14°F ~ 140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-Condensing
Weight	1.2KG
Construction	Metal
Mounting Kit	Wall / Stand / VESA 75 x75 mm
Vibration Test	IEC 60068-2-64, Random, 5~500Hz, 1HR/axis
Shock Test	50Grms, IEC 60068-2-27, Half-Sine, 11ms
System Fan	Fanless
Dimension	255.2 x 169.4 x 33.3 mm

Certifications	
Certification Information	CE, FCC Class B
Software Support	
OS Information	Win10 32 bit, Android 64 bit, Linux 64 bit
Power Requirement	
Power Requirement	DC 12~24V Input
Adapter	Input: 100~240 Vac/50~60 Hz; Output: 65W Adapter (19V @ 3.42A Adapter)
Panel	
LCD Size	10.1", 16:10
Display Type	WXGA
Resolution	1280 x 800
Pixel pitch	0.1695 x 0.1695 mm
Luminance	350 cd/m ²
Contrast ratio	800
Viewing angle	85 (U), 85 (D), 85 (L), 85 (R)
Response time	30 ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Controller	USB Touch
Wireless Communication	