All in One Free Standing Kiosk

43" All-in-One Free-Standing Digital ePoster Kiosk with a Sleek Slim Design. Full HD 1080p resolution 178/178 wide-angle viewing, 450-nit brightness, 1,200:1 contrast ratio

(Model: VSK4300)



All-in-one free-standing digital ePoster kiosk with a sleek, slim design. Great for grabbing attention in busy, high-traffic areas, the VSK4300 comes with a scratch-proof tempered glass faceplate for added durability. Featuring Full HD 1080p resolution, 178°/178° wide-angle viewing, 450-nit brightness, 1,200:1 contrast ratio, and dual 10W stereo speakers, the VSK4300 delivers customized multimedia messaging with vivid clarity. Photo and video files can be played back using the embedded Quadcore media player and 16GB of flash storage, or add your own media player using the convenient media player cradle inside the lockable security door.

FEATURES:

- Free-Standing Design
- Built-in Quad-core Media Player with 16GB Storage
- Internal Scheduler
- Easy Multi-device Management



- 1. Lockable Rear Door
- 2. RS232
- 3. USB Type B
- 4. USB 2.0 Type A
- 5. LAN 6. Audio In
- 7. VGA In
- 8. USB 3.0 Type A (x2)
- 02 03 04 05 06 07 08 09 10 0 11 12 13 14 0 15 0
- 9. HDMI (x2)
- 10. Headphone
- 11. AC In
- 12. Power Switch
- 13. RJ45 Extension
- 14. USB Extensions (x2)
- 15. Media Player Cradle



DISPLAY



450 cd/m2 BRIGHTNESS



INTEGRATED MEDIA PLAYER

SPECIFICATIONS

SI ECITICATIONS	
Display	
Static Contrast Ratio:	1,200:1
Viewing Angles:	178° horizontal, 178° vertical
Orientation:	Portrait
Resolution:	1920 x 1080
Viewable Area (in.):	43
Backlight Life (Hours):	50,000
Response Time (Typical GTG):	12ms
Light Source:	LED
Brightness:	450 cd/m2
Panel Surface:	7H/ 5mm Tempered glass
Aspect Ratio:	16:9
Display Size (in.):	43
Audio:	·
	10W (x2)
Internal Speakers:	1011 (XZ)
Connector: 3.5mm Audio In(1), 3.5mm Audio	Out(1), Ethernet LAN (RJ45)(1),
Connector:	Out(1), Ethernet LAN (RJ45)(1),
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1)	Out(1), Ethernet LAN (RJ45)(1),
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature:	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90%
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD): Packaging (in.):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90% 29.6 x 74.8 x 21.9
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD): Packaging (in.): Physical (in.):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90% 29.6 x 74.8 x 21.9
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD): Packaging (in.): Physical (in.): Dimensions (metric) (WxHxD):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90% 29.6 x 74.8 x 21.9 25.4 x 70.8 x 17.7
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD): Packaging (in.): Physical (in.): Dimensions (metric) (WxHxD): Packaging (mm):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90% 29.6 x 74.8 x 21.9 25.4 x 70.8 x 17.7
Connector: 3.5mm Audio In(1), 3.5mm Audio HDMI 1.4(1), HDMI MHL(1), VGA(1 USB 3.0 Type A(1) Embedded Player: CPU: Power: Voltage: Consumption (typical): Stand-by: Operating Conditions: Temperature: Humidity (non-condensing): Dimensions (imperial) (WxHxD): Packaging (in.): Physical (in.): Packaging (mm): Physical (mm):	Out(1), Ethernet LAN (RJ45)(1),), RS232 In(1), USB 2.0 Type A(2), USB Supported internal media player 100-240 VAC 61W <0.5W 32-104° F (0 - 40° C) 10-90% 29.6 x 74.8 x 21.9 25.4 x 70.8 x 17.7

Weight (metric):		
Gross (kg):	64	
Net (kg):	45	
Controls:		
On Screen Display:	Picture Mode, Contrast, Brightness, Hue, Sharpness, Saturation, Anti- Flicker, Backlight, Screen, Color temperature, Bluelight Filter, Zoom Mode, OverScan, Image NR	
Remote Control:	Sound Mode, Bass, Treble, Balance, Surround, Alone, MHL Auto Switch, Menu Timeout, Data/Time, Off Timer, On Timer, Sleep Time, Set Password, System ID, Lock Keypad, LowerPower Standby, Restore To Default	
Controls Embedded Player:		
Interface:	OSD / Remote Control	
General:		
Regulations: FCC/cTUVus /TUV-Mexico CoC/Mexico Energy/CE EMC/CB/ErP/PSB/RCM/BSMI		
PACKAGE CONTENTS: VSK4300, Power Cord, Remote control with battery, Quick start guide, User's Guide, Door key		
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.		

Warranty: One-year limited warranty on parts, labor and

backlight

