

WB-86

Full-Travel Compact Keyboard

The WB-86 is a sealed, ultra-compact keyboard built for versatility and convenience. Sealed to IP65 standards, the WB-86 is ideal for mobile and point-of-sale applications, or anywhere space is at a premium. The WB-86 features plastic, full-travel key caps, giving it the tactile feel of a standard desktop keyboard, while maintaining the rugged durability of all iKey products. The WB-86 also features individually lit red LED backlit keys and a wear-proof, laser-etched legend.



To learn more, visit our **WB-86 video on YouTube's iKeyKeyBoard Channel:**
[Click Here](#)


Technical Specifications

Certifications	NEMA 4X, IP65, UL90650, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m) Single-Cable USB
Key Switch	MATERIAL: ABS/Polycarbonate KEYCAP MATERIAL: ABS+PC LIFE: Greater than 10 million cycles TRAVEL: 0.115 in. (2.9mm) ACTUATION FORCE: 6.35 oz. +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 200mA @ 5V (from Keyboard port) USB: 200mA@5V (from CPU port)
Comptability	USB KEYBOARD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.4 lbs +/- 0.10 lbs (0.6 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Dimensions	11.06" x 5.16" x 1.01" (w-h-d) 280.9mm x 131.1mm x 25.7mm
Model Numbers	WB-860-USB (with USB cable)
Backlighting	Individual red LED

Features and Benefits

- 86-Key Functionality
- Red LED Backlit Keys
- Full-travel Keystroke
- Sealed and Waterproof
- USB Connectivity

WB-86



KEY SWITCH

MATERIAL: ABS/Polycarbonate
 LIFE: Greater Than 10 Million Cycles
 TRAVEL: 0.115 in.
 ACTUATION FORCE: 6.35 oz. +/- 1.06oz (180g +/- 30g)
 FEEDBACK: Tactile with Mechanical Snap

TEMPERATURE RANGE

STORAGE: -40°F to +194°F (-40°C to +90°C)
 OPERATING: -40°F to +158°F (-40°C to +70°C)

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
 FREQUENCY RANGE: 20Hz-2Khz
 DURATION OF TEST PER AXIS: 3 hours

POWER

PS2: KEYBOARD: 200mA@5V (from Keyboard port)
 USB: 200mA@5V (from CPU port)

HUMIDITY

100% Humidity Resistant

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.4 ± 0.10 lbs (0.6 ± 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

Part Number: WB-86	Drawing Number: PAD0265	Sheet: 1 OF 1
Drawing Title: WB-86-MKT (REV 1.1)	Revision: 1.1	Date: 8.15.2011 TWH



Distributed by:
 i-Tech Company LLC
 TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com