

IP65 FRONT PANEL MOUNT (Metal-5mm)

Wide 10.1" LCD monitor, 1024 x 600, 450nits, VGA Input
Rear OSD, including rear screw/Clamp/VESA Mount

MODEL: CPMW1010IP




FEATURES:

- IP65 Front Panel Mount (Metal-5mm)
- VGA Input, Rear OSD
- Rear Screw/Clamp/VESA Mount
- Resolution: 1024x600
- Brightness: 450nits



SPECIFICATIONS:


Panel Size	10.1"
Active Display Area(mm)	222.72 (H) x 125.28 (V)
Resolution	1024 x 600
Brightness(cd/m2)	450 (Typical)
Contrast Ratio	800:1 (Typical)
Viewing Angles(CR>=10 L/R/U/D)	-80~80(H) ; -80~75(V)
Display Colors	16.7M (8 bits/color)
Standard Input Signal	1 x VGA (D-sub 15) 1 x HDMI (Type-A)
Touch Screen(Optional-1)	Resistive Touch Protective Glass
Touch Interface	USB / RS232
Audio / Speakers (Optional)*	Audio line in (3.5mm) + Speaker x2
OSD	5 Keys: -, +, Power, Esc, Enter
Power Input	12V DC input (2.5ψ) with external AC-DC Adapter (100V~240V)
Power Consumption	10W typical, Normal operation
Operating temperature	0~50°C
Storage Temperature	-10~60°C
Accessories	Power AC-DC Adapter(100V~240V) VGA cable (1.8m) HDMI cable (2m)



1. VGA
2. HDMI
3. 12V DC In

I/O Optional	
Optional 1*	1 x VGA (D-sub 15) 1 x HDMI (Type-A) 1 x DVI-D
Optional 2*	1 x VGA (D-sub 15) 1 x DVI-D 1 x S-Video 1 x Composite

MECHANICAL DRAWING:



CUT OUT : 239 x 170mm

* Note: The mechanical drawing may change when adding touch screen.
Please contact our sales representative if you need further product information.