

Teleprompter High Brightness LCD Display

15" Teleprompter High Brightness LCD Display,
Reverses images internally with no special
equipment or software needed.
(Model: PCH1500SHB)



Features:

- 15" LCD
- VGA+ S-Video + Composite (BNC connections) + DVI
- G2A Board (G2A221)
- No touch ; No glass
- Stand chassis and standard OSD + Front IR sensor
- Standard Rear OSD with Remote controller (w/Flip button)

Specifications:

Viewable Size Image	15"
Active Display	204.128(H) x 228.096(V)
Area(mm)	
Pixel Pitch(mm)	0.297(H) x 0.297(V)
Number of Pixels	1024 x 768
Contrast Ratio	700:1 (typ.)
Display Color	16.2M
Brightness(cd/m)	1500
Viewing Angle(CR>=10)	-80~80(H);-70~70(V)
Synchronization Range	31.5~60.0KHz/60~75Hz
Horizontal/Vertical	
Recommended	1024x768@60Hz,75Hz
Resolution	
Signal Connector	15 pin D-Sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)

Mirror Image Features



**Reverses images internally - no special equipment
or software needed!!**

Power Consumption	35W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite (BNC)
Optional DVI Input	Yes
Optional Touch Screen	Yes, Resistive, Capacitive, SAW

Model: Photo Gallery



Mechanical Drawings:

