



Teleprompter LCD Display

Reverses images internally with no special equipment or software needed

19" LCD Display, 400 nits SXGA 1280(H) x1024(V) resolution.
VGA + composite- BNC +DVI

Model: **PCH1900S**



Mirror Image Features



Reverses images internally - no special equipment or software needed!!

Specifications:

Viewable Size image	19"	Recommended Resolution	1280x1024@60Hz, 75Hz
Active Display Area (mm)	376.32(H)x301.06(V)	Signal Connector	15 pin D-Sub
Pixel Pitch(mm)	0.294(H)x0.294(V)	Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Number of Pixels	1280x1024	Power Consumption	35W typical, normal operation
Contrast Ratio	550:1(typ.)	Power Management	VESA DPMS Compliant
Display Colors	16.7M (8bits/color)	Plug & Play	VESA DDC 1/2B
Brightness(cd/m)	400	Optional Video Input	S-Video, Composite
Viewing Angle(CR>=10)	-70~70(H);-60~75(V)	Optional DVI Input	Yes
Synchronization Range		Optional Touch Screen	Resistive,Capacitive,SAW
Horizontal/Vertical	31.5~80.0KHz/60~75Hz		
Horizontal/Vertical			



Mechanical Drawings:

