



Specifications

| | |
|---|---|
| Model Name | WCH1040T2 |
| Viewable Size image | 10.4" |
| Active Display Area (mm) | 210.4(H) x 157.8(V) |
| Pixel Pitch(mm) | 0.0685 (H) x 0.2055 (V) |
| Number of Pixels | 1024x768 |
| Contrast Ratio | 1200:1 (typ.) |
| Display Colors | 16.2M (8bits/color) |
| Brightness(cd/m) | 350 (typ.) |
| Viewing Angle(CR>=10) | -88~88 (H); -88~88 (V) |
| Synchronization Range Horizontal/Vertical | 31.5~46.9KHz / 60~75Hz |
| Recommended Resolution | 1024x768@60Hz,75Hz |
| Signal Connector | 15 pin D-Sub |
| Power Source | 12V DC in, with External AC to DC Adapter (100~240V AC) |
| Power Consumption | 15W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | S-Video, Composite |
| Optional DVI Input | No |
| Optional Touch Screen | Resistive, SAW, IR |



Remarks: WCH1040T2 series= VGA input only
WCH1040T2AV series= VGA+Video Input

