

T-Series 12.1" Panel PC

(Intel Pentium M / Celeron M Platform)

Model no.: WCHC1210M7-I

System Specifications:

TFT Characteristics

Pixel Number : 1024 x 768
Brightness : 450 cd/m (typ.)
Contrast Ratio : 700 : 1 (typ.)
Viewable Angles : -80~80(H); -80~80(V)
Max Colors : 262,144 colors

Environmental Considerations

Operating Temperature : 0 deg.C to 50deg.C
Operating Humidity : 30% to 90% (non condensing)



Chassis

SBC Specifications

Processor : Socket 479 for Intel Pentium M / Celeron M
up to 2 GHz
BIOS : Award 4Mbit Flash
System Chipset : Intel 855GME + ICH4
Memory Slot : 1 x DIMM, Max 1GB DDR 200/266/333
Graphic Chipset : Intel 855GME Integrated (64MB shared)
IDE : 2 x IDE (UDMA 33/66/100)
KB / Mouse : 2 x PS/2
Ethernet : 2 x RJ-45
Audio : Build in AC97 Codec
USB : 6 x USB 2.0
Serial : 3 x RS232(1xOptional), 1 x RS232/422/485
Expansion Slot : 1 x Mini PCI, 1 x PCI*

* A customized housing is needed if you would like to have the PCI expansion.

Output Connectors

Ethernet LAN : 2 x RJ 45-10/100/1000 Mbps
Keyboard / Mouse : 2 x PS/2
COM : 2 x RS232, 1 x RS232/422/485 9P DSUB (male)
Audio : 1 x Audio Jack(Line-Out, Line-In, Mic in)
USB : 4 x USB Type-A Receptacle
VGA Out : 1 x VGA (female)

Order Options

SBC	PANEL PC
CPU : Celeron M 1.5GHz* Pentium M 1.73GHz (Optional)	Mechanical : Open Frame Panel Mount (5mm bezel) IP65 (10mm bezel) Chassis
RAM : 256 MB DDR* 512 MB DDR(Optional) 1 GB DDR(Optional)	Touch : 5 Wires Resistive(Optional) OS : Windows XPE(Optional) Windows XP (Optional) Linux(Optional)
Storage : 2.5"40 GB HDD* 1 GB Compact Flash(Optional)	
* Default	

Power Specification

Power Input : 12V DC IN (Lockable Power Jack)
Power Consumption : 65W (typ.)(Max.backlight & high CPU load)

Accessories

External Power Supply 80W w/power cord



i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com

