

## Sunlight Readable Chassis Monitor

15"

### Specifications



Model Name	WCHH1500A1
Viewable Size Image	15"
Active Display Area(mm)	204.128(H)x228.096(V)
Pixel Pitch(mm)	0.297(H)x0.297(V)
Number of Pixels	1024x768
Contrast Ratio	500:1 (typ.)
Display Color	16.2M(6bits+FRC)
Brightness(cd/m <sup>2</sup> )	550
Viewing Angle(CR>=10)	-70~70(H);-50~70(V)
Synchronization Range	31.5~60.0KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	1024x768@ 60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	AC 100~240V, Universal, ±10%
Power Consumption	35W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	No
Optional Touch Screen	Resistive, Capacitive, SAW

Remarks:WCHH1500A1 series= VGA input only

WCHH1500A1AV series= VGA+Video Input

#### Outdoor readability

Ambient light(nit)	Brightness measure Angle	10,000	30,000	80,000
Brightness gain(BL0n)(nit)	35°	625	780	1,150
Reflectance(net)(%)		1%	0.98%	0.9%

### Mechanical Drawing

