

Chassis Monitor

Sunlight Readable Chassis Monitor



20.1"

Specifications

Model Name	WCHH2010A2
Viewable Size Image	20.1"
Active Display Area (mm)	408.0(H)x306.0(V)
Pixel Pitch (mm)	0.51(H)x0.51(V)
Number of Pixels	1600x1200(UXGA)
Contrast Ratio	700:1 (typ.)
Display Color	16.7M(8bit/colors)
Brightness (cd/m ²)	312.5
Viewing Angle (CR >=10)	-85~85(H); -85~85(V)
Synchronization Range	31.5~80KHz/60~85Hz
Horizontal/Vertical	
Recommended Resolution	1600x1200@ 60Hz
Signal Connector	15 pin D-S ub
Power Source	AC 100~240V, Universal, ±10%
Power Consumption	60W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	SAW

Remarks: WCHH2010A2= VGA Input only

WCHH2010A2AV= VGA+Video Input

Outdoor readability

Ambient light (nit)	Brightness measure			
	Angle	10,000	30,000	80,000
Brightness gain (BL0n) (nit)	35°	312.5	456	680
Reflectance (net) (%)		0.7%	0.68%	0.45%

**i-TECH
COMPANY**
www.i-techcompany.com
Toll Free: 1-888-483-2418
USA: 1-510-429-9288
Fax: 1-510-372-2736

