

Sunlight Readable LCD

Sunlight Readable LCD



26" (16:9)

Specifications

**RoHS
COMPLIANT
2002/95/EC**

Model Name	WCHHW2600A2
Viewable Size Image	26" (16:9)
Active Display Area (mm)	575.769(H)x323.712(V)
Pixel Pitch (mm)	0.4215(H)x0.4215(V)
Number of Pixels	1366x768
Contrast Ratio	800:1 (typ.)
Display Color	16.7M (8bit/colors)
Brightness (cd/m ²)	625
Viewing Angle (CR>=10)	-88~88(H); -88~88(V)
Synchronization Range	31.5~47.6KHz/50~60Hz
Horizontal/Vertical	
Recommended Resolution	1366x768@60Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	145W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	SAW
Optional protection glass (refraction rate < 0.5%)	UV glass / clear type glass

Outdoor readability

Ambient light (nit)	Brightness measure Angle	10,000	30,000	80,000
		35°	625	820
Brightness gain (BL0n) (nit)		1%	0.98%	0.9%
Reflectance (net) (%)				

Mechanical Drawing

