

Open Frame LCD




Specifications	
Model Name	WOP1210A1
Viewable Size image	12.1"
Active Display Area (mm)	246.0(H)x184.5(V)
Pixel Pitch(mm)	0.3075(H)x0.3075(V)
Number of Pixels	800x600
Contrast Ratio	700:1(typ.)
Display Color	16.2M (8bits/colors)
Brightness(cd/m2)	450(typ.)
Viewing Angle(CR>=10)	--80~80 (H); -65~75 (V)
Synchronization Range (Horizontal / Vertical)	31.5~46.9KHz/60~75Hz
Recommended Resolution	800x600@60Hz, 75Hz
Signal Connector	15 pin D-Sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	15 W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	No
Optional Touch Screen	Resistive, Capacitive



Remarks: WOP1210A1 series= VGA input only
WOP1210A1AV series= VGA+Video Input

MECHANICAL DRAWING



*Note: this is a simplified drawing and some components are not marked in detail.
Please contact our sales representative if you need further product information.