



Open Frame LCD




| Specifications | |
|--|---|
| Model Name | WOP1500C3 |
| Viewable Size image | 15" |
| Active Display Area (mm) | 304.1(H)x228.1(V) |
| Pixel Pitch(mm) | 0.297(H)x0.297(V) |
| Number of Pixels | 1024x768 |
| Contrast Ratio | 500:1(typ.) |
| Display Color | 16.2M(6bit+FRC) |
| Brightness(cd/m2) | 250(typ.) |
| Viewing Angle(CR>=10) | -70~70(H); -60~65(V) |
| Synchronization Range (Horizontal / Vertical) | 31.5~60.0KHz/60~75Hz |
| Recommended Resolution | 1024x768@60Hz,75Hz |
| Signal Connector | 15 pin D-Sub |
| Power Source | 12V DC in, with External AC to DC Adapter (100~240V AC) |
| Power Consumption | 25W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | S-Video, Composite |
| Optional DVI Input | Yes |
| Optional Touch Screen | Resistive, Capacitive, SAW, IR |



Remarks: WOP1500C3 series= VGA input only
 WOP1500C3AV series= VGA+Video Input

MECHANICAL DRAWING





*Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

UNIT:mm

