Specifications	
Model Name	WOP1900M2
Viewable Size image	19"
Active Display Area (mm)	376.32 (H) x 301.056 (V)
Pixel Pitch(mm)	0.294(H)x0.294(V)
Number of Pixels	1280x1024
Contrast Ratio	1300:1(typ.)
Display Color	16.7M (8 bits/colors)
Brightness(cd/m2)	300(typ.)
Viewing Angle(CR>=10)	-89~89(H);-89~89(V)
Synchronization Range (Horizontal / Vertical)	31.5~80.0KHz/60~75Hz
Recommended Resolution	1280x1024@60Hz, 75Hz
Signal Connector	15 pin D-sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	41W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive,Capacitive,SAW,IR

Remarks: WOP1900M2 series= VGA input only
WOP1900M2AV series= VGA+Video Input

MECHANICAL DRAWING



UNIT: mm

*Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com