

Rugged 24" Marine Panel Mount LCD Display

Model: WPM-MAR-W2400A1

FEATURES:

- Adjustable dimming knob to control backlight brightness from almost 0% to 100%
- Aluminum housing with powder coating design, meeting IP65 standards (IP54 for rear)
- Equipped with a 24V DC Isolated Power Module
- High-Quality Touchscreen with option for AR Protection Glass
- User-friendly front panel OSD control for Marine Display
- Enhanced resistance to shock and vibration



SPECIFICATIONS


DISPLAY			
Resolution	1920x1080	Size	24 inches
Contrast Ratio	5000:1	Panel Brightness	300 nits
View Angles	89,89,89,89	Active Area	531.36x298.89 mm
Touch / Glass	Resistive Touch Screen AR Glass (Optional)	Display Color	16.7M Colors
ENVIRONMENT			
Operating Humidity	5% to 95%	Operating Temperature	15 ~ 55°C
IP Rating	IP65 (Front Side)	Shock	15G,11ms duration
Vibration	0.7g@DNVGL CG0339 (Class A)		
CERTIFICATION			
Certification	DNVGLCG0339, IEC60945 4th, IACS E10, CE, FCC		
IO PORTS			
Serial Port	1 x RS232 for Remote Control 1 x RS232/USB for Touch Screen	Video	1 x VGA 1 x DVI-D 1 x Composite 1 x S-Video
MECHANICAL			
Dimension	593 x 356.7 x 62.7	Mounting	VESA Mount/ Panel Mount
Enclosure	Metal Housing with Aluminum Bezel	Cooling System	Fanless Design
Weight	9.7 kg	Cut out	566 x 362 mm
POWER			
Power Rating	24V DCin with Isolation (Approval by Certificate) 9~36V DC Input Acceptable	Consumption	50W (Typical)

ACCESSORIES	
Accessories	1 x User Manual, 1 x CD for Touchscreen Driver Tools, 1 x DVI Cable, 1 x VGA Cable, 1 x RS232 Serial Cable, 1 x SVideo Cable, 1 x Composite Cable.
CONTROL	
Button	8 key: Esc/PIP, Auto adjustment, Left, Right/Source, OK/Menu, Up, Down, Power, 1 x The Dimming Knob

**Specifications subject to change without notice, not responsible for typographical errors.*

MECHANICAL DRAWINGS

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.



Drawing No.: WPM-MAR-W2400A1-03262024-V1