

Panel Mount LCD



Specifications

Model Name	WPMW2200M1 (Standard) WPMW2200M1-S (with SAW Touch)
Viewable Size image	22"(16:10)
Active Display Area (mm)	473.76(H)x296.1(V)
Pixel Pitch(mm)	0.282mmX0.282mm
Number of Pixels	1680x1050
Contrast Ratio	1000:1 (typ.)
Display Color	16.7M(8bit/color)
Brightness(cd/m2)	300(typ.)
Viewing Angle(CR>=10)	-80~80(H); -80~80(V)
Synchronization Range (Horizontal / Vertical)	31.5~80.0KHz/60~75Hz
Recommended Resolution	1680x1050@ 60Hz
Signal Connector	15 pin D-sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	60W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive,SAW(need special housing)



Remarks: WPMW2200M1-S series= VGA input only
WPMW2200M1-SAV series= VGA+Video Input



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com

