

# Rugged Completely Sealed IP66/NEMA4X Stainless Steel


Rugged Completely Sealed IP66/NEMA4X  
Stainless Steel Chassis/Surface Mount, Water/Dust  
proof 10.4" LCD monitor, 1024x768, 1000 nits,  
without speaker VGA input, Rear OSD, VESA  
Mount, with 5 Wire Resistive Touch Screen and USB  
Controller

**Model: ECH1040XHB-SIP-TR**



**ECHXXX-SIP Series:** Rugged Completely Sealed IP66/NEMA4X Stainless Steel Chassis/Surface Mount  
(Optional Integrated All-in-One PC Fanless and Touchscreen Solution)

## FEATURES HIGHLIGHTS:



Water Proof Solution, Full IP/NEMA4 Rating  
front and back  
Stainless and Aluminum Housing Chassis Design

Glass Protective Glass at front

Optional High Brightness and Touch screen



- IP65 Water and Dust proof connection for a higher protection
- All Connectors are facing back with IP66 water proof connectors

# Stainless Steel Chassis LCD Monitor

## FEATURES:

- Modular mechanism design provides flexible product configuration and easy maintenance.
- Stainless Steel Enclosure.
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- Complete custom design/solution for OEM customers


## SPECIFICATION:

<b>Panel</b>	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size	4 : 3 / 10.4" viewable diagonal area		
	Active Area / Pixel Pitch	210.4(H) x 157.8(V) mm / 0.2055(H) x 0.2055(V) mm		
	Native Resolution / Colors	1024(H) x 768(V) / 16.2 M		
	Brightness / Contrast	1000 cd/m2 (typ) / 600 : 1		
	Response Time	≤ 25 ms		
	Viewing Angle (typical)	H:160° (- 80° ~ + 80°) , V: 140° (- 70° ~ + 70°)		
	Light Source	LED backlight, Long life, 35,000 hrs (typ)		
<b>Input Sources</b>	PC System	Signal	Analog RGB (0.7/1.0 V <sub>D.D</sub> , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F <sub>H</sub> : 30 - 82Khz , F <sub>V</sub> : 50 -75Hz	
	Audio System	N / A		
<b>Input Terminals</b>	1 x VGA (15 Pin Female D-Sub), 1 x PC Audio (Stereo Headphone Jack), 1 x DC Power Plug			
<b>Convenient Features</b>	Auto Calibration , Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)			
<b>Power</b>	12V DC in			
<b>Power Consumption</b>	Operation / Power Saving	18 watt , < 2 watt (Support DPMS)		
<b>Operating Condition</b>	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation)		
<b>Storage Condition</b>	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F), 10% ~ 90% (no condensation)		
<b>Certification</b>		FCC,CE		
<b>Dimensions</b>	Physical	Please refer to Drawing		
	Carton	W x H x D = TBD		
<b>Weight</b>	N.W. / G.W.	6 Kgs / 7 Kgs		
<b>Container Loaded</b>	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)		

<b>Options</b>	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sunlight Readable	Light Sensor
	Protected glass			Auto-Dimming

# Stainless Steel Chassis LCD Monitor

## MECHANICAL DRAWING:



# Stainless Steel Chassis LCD Monitor

## LCD OPTIONS:



### LED Backlight Options

Introducing LED backlight options for monitors for energy efficiency and a brighter screen.



### TouchScreen Options

Our LCD has a wide selection option to choose which touchscreen technology suits for you.

	Four-Wire Resistive	Five-Wire Resistive	Capacitive
<b>PRODUCT SIZE</b>	1.7" - 24"	10.4" - 24"	12" - 24"
<b>TOUCH LIFE</b>	1 - 2 million touches	30 - 35million touches	100 million touches
<b>SCRATCH RESISTANCE</b>	Hard Coated	Hard Coated	Hard Coated (SiO <sup>2</sup> )
<b>CONTAMINANT RESISTANCE</b>	Resists moisture, dirt, vinegar, ammonia based food products and cleansers	Resists moisture, dirt, vinegar, ammonia based food products and cleansers	Resists moisture, dirt, vinegar, ammonia based food products and cleansers
<b>INPUT METHOD</b>	Finger, Gloved Hand, Stylus	Finger, Gloved Hand, Stylus	Finger
<b>CONTROLLER</b>	USB, RS232	USB, RS232	USB, RS232



### VIDEO Input Options:

For Video inputs options:

DVI, DVI+HDMI, SVideo+AV, SVideo+AV+DVI, AV+Looping, DVI+AV+Looping, HD-SDI, BNC(PAL/NTSC)



### Optical Bonding Options

- Optical Bonding provides the best reduction of ambient light washout of any commercially available enhancement technology.
- Optical Bonding has a lower cost than most other competing technologies.
- Optical Bonding offers superior ruggedization, enhancing the display durability under vibration, shock and other environmental extremes.



### RS-232 Remote Control Options

**Remote Control Protocol: Command Code to set system**



### 9-36V DC Input Options

iTech offers a selection of DC input from 9V to 36V



### Light Sensor and Motion Sensor Options

iTech LCD offers Light and Motion Sensor

### Privacy Filter

Front Glass Options:

- Anti Reflective AR Glass 3mm
- Anti Reflective AR Glass 6mm Vandal-Resistance
- Anti Reflective AR Glass 8mm Vandal-Resistance
- Anti Glare AG Glass 3mm