

Industrial IP66 Chassis MOUNT LCD Monitor



32" IP66 Chassis Mount LCD Monitor
 2560 x 1440, LED 350 nits, 1 x VGA + 5 x HDMI + 1 x DP input

Model: ECHW32002K-SIP



FEATURES:

- High 2K resolution provides an exceptional experience regardless of any application
- Modular construction for more flexibility in terms of product configuration as well easy maintenance
- A brightness sensor for auto adjustment of the screen so that it's neither too bright nor too dark
- Robust aluminum housing to withstand rugged applications
- Optional build-in touch screen functionality for an interactive application
- Optional protective glass to keep dust, dirt, and moisture away from the display
- Standard VGA connector but also available with optional AV, SV, and AV-Looping
- Energy-efficient based on advance power management
- Customizable design available upon request for OEM customers



OPTIONS:

Touch: Resistive, Capacitive, SAW, Infrared, and Protected glass

Video/TV: SV + AV, SV + AV + AV_Looping, SV + AV + TV

Enhanced Panel: Panel with LED backlight, High brightness panel, Wide Temperature, Sunlight Readable

Others optional features: Digital Signage (Standalone), Networking Digital Signage, Motion Sensor, Light Sensor, Auto-Dimming

SPECIFICATIONS:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 32" viewable diagonal area	
	Active Area / Pixel Pitch	708.48(H) x 398.52(V) mm / 0.276(H) x 0.276(V) mm	
	Native Resolution / Colors	2560(H) x 1440(V) / 1.07B	
	Brightness / Contrast	350 cd/m2 (typ) / 1000 : 1	
	Response Time	≤ 6 ms (G-to-G)	
	Viewing Angle (typical)	H.178° (- 89o ~ + 89o) , V. 178o(- 89o ~ + 89o)	
	Light Source	LED backlight, Long life, 35,000 hrs (typ)	
	Input Sources	PC System	Signal
Sync			Separate Sync, Composite Sync, Sync On Green
Frequency			F _h : 30 - 82Khz , F _v : 50 -75Hz
Audio System		N / A	
Input Terminals	1 x VGA , 5 x HDMI, 1 x DP , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)		
Power	Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz		
Power Consumption	Operation / Power Saving	73.75 watt , < 1 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	Please refer to Drawing	
	Carton	W x H x D = TBD	
Weight	N.W. / G.W.	14.5 Kgs / 16 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)	

MECHANICAL DRAWING:

