

Industrial Panel PC IP65 Front

Panel PC IP65 Front, 26" LCD monitor, 1920x1080, 400nits
Side OSD, including rear screw/Clamp/VESA Mount with
Capacitive Touch Screen , Intel Core H61 i5-2390T Processor
(3M Cache, 3.5 GHz, 2C/4T, 35W) 4GB Memory,
500GB HDD, 2 x COMs (RS232 / RS422 / RS485), 1xVGA,
1xHDMI, 4xUSB2.0, 2xSATA, 1xPS/2, Audio, 1xMini-PCIe,
2xGbE LAN



(Model: EMCW2600-i5-TC)

Features:

- 26" LCD panel, 1920 x 1080, 400 nits
- Intel® Core™ i7/i5/i3/ Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out



Specifications:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	wide / 26" viewable diagonal area
	Active Area / Pixel Pitch	576.0(H) x 324.0(V)mm / 0.3(H) x 0.3 (V)mm
	Native Resolution / Color	1920(H) x 1080(V) / 16.7 Million
	Brignthess / Contrast	400 cd/m (typ) / 2000 : 1
	Response Time	^ 8 ms
	Viewing Angle (Typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)
	Light Source	CCFL, Long life, 50,000 hrs (typ)
System	CPU	Intel® Core™ i7/i5/i3/ Celeron Processor
	BIOS	UEFI
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
	HDD	4 x SATA2
	I/O Ports	1 x VGA
		2 x COM
		1 x HDMI
		6 x USB(2.0)
		2 x LAN
		Audio Line In
Expension	1 x Mini PCI-E (Half Size)	
Power	Power Input Power	ATX PWR (24+4 pin)
	Consumption	###Watt, <1 Watt
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)
		0%~95% (non-

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Photo Gallery:



Mechanical Drawing:

