

Industrial Panel PC IP65 Front

Panel PC IP65 Front, 32" LCD monitor, 1920x1080, 400nits
Side OSD, including rear screw/Clamp/VESA Mount with
Capacitive Touch Screen , Intel Core H61 i5-2390T Processor
(3M Cache, 3.5 GHz, 2C/4T, 35W) 4GB Memory,
500GB HDD, 2 x COMs (RS232 / RS422 / RS485), 1xVGA,
1xHDMI, 4xUSB2.0, 2xSATA, 1xPS/2, Audio, 1xMini-PCIe,
2xGbE LAN



(Model: EMCW3200-i5-TC)

Features:

- 32" LCD panel, 1920 x 1080, 400 nits
- Intel® Core™ i7/i5/i3/ Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out



Specifications:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspec Ratio / Size	wide / 32" viewable diagonal area		
	Active Area / Pixel Pitch	698.4(H) x 392.9(V) mm / 0.3638(H) x 0.3638(V) mm		
	Native Resolution / Color	1920(H) x 1080(V) / 16.7 Million		
	Brighthess / Contrast	400 cd/m (typ) / 3000 : 1		
	Response Time	^ 8 ms(G-to-G)		
	Viewing Angle (Typical)	H. 178° (- 89° ~ + 89°) , V. 178° (- 89° ~ + 89°)		
	Light Source	CCFL, Long life, 50,000 hrs (typ)		
System	CPU	Intel® Core™ i7/i5/i3/ Celeron Processor		
	BIOS	UEFI		
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory		
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)		
	HDD	4 x SATA2		
	I/O Ports	1 x VGA		
		2 x COM		
		1 x HDMI		
		6 x USB(2.0)		
		2 x LAN		
		Audio Line In		
	Expension	1 x Mini PCI-E (Half Size)		
Power	Power Input Power	ATX PWR (24+4 pin)		
	Consumption	###Watt, <1 Watt		
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)		
	Humidity	0%~95% (non-		

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Mechanical Drawing:

