

## Widescreen Display

All in one PC Widescreen Display Chassis Mount, 21.5" LCD monitor, 1920x1080, 300nits Intel® Core™ i5-540E Processor (3M Cache, 2.53 GHz), up to 8 GB, 4GB Memory and 500GB HDD 3.5" SATA

(Model: [EPCW2150HDI5](#))



### Features:

- 21.5" LCD panel, 1920x1080, 300 nits
- Intel® Core™ i7/i5/Celeron Processor
- Intel® QM57
- 2 x DDR3 SO-DIMM Up to 8GB 800/1066 MHz SDRAM
- 1 x VGA, 1 x DVI, 6 x USB, 2 x COM, 2 x LAN
- 1 x PS2, Mic-in, Line-in, Line-out

### Specification:

|               |                           |  |  |
|---------------|---------------------------|--|--|
| Panel         | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating |  |
|               | Aspec Ratio / Size        | Wide / 21.5" viewable diagonal area                |  |
|               | Active Area / Pixel Pitch | 476.64(H) x 268.11(V) mm / 0.248(H) x 0.248(V) mm  |  |
|               | Native Resolution / Color | 1920(H) x 1080(V) / 16.7 Million                   |  |
|               | Brignthess / Contrast     | 300 cd/m (typ) / 1000 : 1                          |  |
|               | Response Time             | ^ 5 ms   |  |
|               | Viewing Angle (Typical)   | H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)   |  |
|               | Light Source              | CCFL, Long life, 50,000 hrs (typ)                  |  |
| System        | CPU                       | Intel® Core™ i7/i5/Celeron Processor: FSB 1066MHz  |  |
|               | BIOS                      | AMI  |  |
|               | System / Graphic Chipset  | Intel® QM57 / HD Graphics Integrated               |  |
|               | System Memory             | 2 x DDR3 SO-DIMM Up to 8GB 800/1066 MHz SDRAM      |  |
|               | HDD                       | 6 x SATA   |  |
|               | I/O Ports                 | 1 x VGA 1 x DVI                                    |  |
|               |                           | 6 x USB  |  |
|               |                           | 2 x COM  |  |
| 2 x LAN       |                           |  |  |
| Expansion     | 1x(K/B and Mouse)         |  |  |
|               | Mic-in, Line-in, Line-out |  |  |
| Power         | Power Input Power         | 24V DC-IN (4-Din Connector)                        |  |
|               | Consumption               | 76 Watt, <1 Watt                                   |  |
| Environmental | Operating Temperature     | - 5°C~60°C (23°F~140°F)                            |  |
|               | Operating Humidity        | 0%~95% (non-condensing)                            |  |

|         |                       |                       |           |                            |
|---------|-----------------------|-----------------------|-----------|----------------------------|
| Options | Touch                 | Enhanced Pane         | Other     |                            |
|         | Resistive(With Glass) | High Brightness Panel | WiFi      | Networking Digital Signage |
|         | Capactive             | Panel-LED Backlight   | 3G        | Web Cam                    |
|         | SAW                   | Wide Temperature      | Bluetooth | Motion Sensor              |
|         |                       | Wide Viewing Angle    | RFID      | Auto LightSensor           |
|         |                       | Sunlight Readable     |           | Auto-Dimming               |

Mechanical Drawings:

