

# All in One PANEL PC with Touch

## Widescreen Display

All in one PC Widescreen Display Chassis Mount, 21.5" LCD monitor with Resistive Touch USB Controller, 1920 x 1080, 300 nits Intel® H61 Core™ i7-3770T Processor (8M Cache, 3.7 GHz, 4C/8T, 45W) installed,, 4GB Memory and 250GB HDD 3.5" SATA 1xVGA, 1xHDMI, 4xUSB2.0, 2xSATA, 1xPS/2, Audio, 1xMini-PCIe, 2xGbE LAN

(Model: EPCW2200i7-TR)

- 21.5" LCD panel, 1920x1080, 1000 nits
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out
- Intel® Core™ i7/i5/i3/ Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)

### Specification:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspec Ratio / Size	Wide / 21.5" viewable diagonal area	
	Active Area / Pixel Pitch	476.64(H) x 268.11(V) mm / 0.248(H) x 0.248(V) mm	
	Native Resolution / Color	1920(H) x 1080(V) / 16.7 Million	
	Brignthess / Contrast	1000 cd/m(typ) / 1000 : 1	
	Response Time	^ 5 ms	
	Viewing Angle (Typical)	H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)	
	Light Source	LED, Long life, 35,000 hrs (typ)	
System	CPU	Intel® Core™ i7/i5/i3/ Celeron Processor	
	BIOS	UEFI	
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory	
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)	
	HDD	4 x SATA2	
		I/O Ports	1 x VGA
			2 x COM
			1 x HDMI
6 x USB(2.0)			
2 x LAN			
Audio Line In			
Expansion	1 x Mini PCI-E (Half Size)		
Power	Power Input Power	ATX PWR (24+4 pin) 76	
	Consumption	Watt, <1 Watt	
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)	
	Operating Humidity	0%~95% (non-condensing)	

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
	Sunlight Readable		Auto-Dimming	

**Mechanical Drawing:**

