

# ZERO BEZEL CHASSIS LCD

**10.4" Zero Bezel Chassis LCD Monitor**  
**800 x 600, LED 350 nits, 600:1, VGA input**  
**Wide Temperature**

**MODEL: EZRH1040WTWV**



## FEATURES:

- Modular construction for more flexibility in terms of product configuration as well easy maintenance
- Optional build-in touch screen for interactive application
- VGA connector with optional AV,SV,AV-Looping
- Available with auto-brightness sensor offers application in day and night
- Complete custom design/solution for OEM customers

## SPECIFICATIONS:

|                            |  |  |   |
|----------------------------|--|--|---|
| <b>Panel</b>               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating         |   |
|                            | Aspect Ratio / Size  | 4 : 3 / 10.4" viewable diagonal area                       |   |
|                            | Active Area / Pixel Pitch  | 211.2(H) x 158.4(V) mm / 0.264(H) x 0.264(V) mm            |   |
|                            | Native Resolution / Colors   | 800(H) x 600(V) / 262 K                                    |   |
|                            | Brightness / Contrast  | 350 cd/m <sup>2</sup> (typ) / 600 : 1                      |   |
|                            | Response Time  | < 35 ms  |   |
|                            | Viewing Angle (typical)  | H. 160° (- 80° ~ + 80°) , V. 120° (- 60° ~ + 60°)          |   |
|                            | Light Source   | LED backlight, Long life, 35,000 hrs (typ)                 |   |
| <b>Input Sources</b>       | PC System  | Signal   | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                            |  | Sync   | Separate Sync, Composite Sync, Sync On Green            |
|                            |  | Frequency  | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                            | Audio System   | 2W speaker x 2   |   |
| <b>Input Terminals</b>     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |  |   |
| <b>Convenient Features</b> | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |  |   |
|                            | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |  |   |
| <b>Power</b>               | 12V DC in  |  |   |
| <b>Power Consumption</b>   | Operation / Power Saving   | 9.375 watt , < 2 watt (Support DPMS)                       |   |
| <b>Operating Condition</b> | Temperature / Humidity   | - 30°C ~ 70°C (22°F ~ 158°F) , 10% ~ 90% (no condensation) |   |
| <b>Storage Condition</b>   | Temperature / Humidity   | - 30°C ~ 80°C (22°F ~ 176°F) , 10% ~ 90% (no condensation) |   |
| <b>Certification</b>       | FCC , CE   |  |   |
| <b>Dimensions</b>          | Physical   | Please refer to Drawing                                    |   |
|                            | Carton   | W x H x D = TBD  |   |
| <b>Weight</b>              | N.W. / G.W.  | 3.5 Kgs / 4.5 Kgs  |   |
| <b>Container Loaded</b>    | 20ft / 40ft / 40ft HQ  | TBD (Sets , By pallet)                                     |   |

## OPTIONS:

- **Touch:** Projected Capacitive Touch and Protected glass
- **Video/TV:** Video/TV, SV + AV, SV + AV + AV\_Looping, SV + AV + TV
- **Enhanced Panel:** Panel with LED backlight, High brightness panel, Wide Temperature, Sunlight Readable
- **Others optional features:** Digital Signage (Standalone), Networking Digital Signage, Motion Sensor, Light Sensor, Auto-Dimming

**MECHANICAL DRAWINGS:**

