



24" Wide LCD monitor , Resolution 1920 x 1200, 300 nits,with 3mm AR glass, Intel Core i5-3610ME Processor (3M Cache, 3.30 GHz) installed Integrated in Fanless , Memory 4GB, 32 GB SSD, Water proof cable: 1 x COM, 1 x VGA, 2 x USB, 1 x LAN, 1 x Power

Model: ECHW2400-SIP-i5

FEATURES:

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Core i3 / i5 / i7 Processors
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x COM, 1 x VGA, 2 x USB, 1 x LAN, 1 x Power
- IP66 Compliant



SPECIFICATIONS:

| | | |
|----------------------------|----------------------------|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspect Ratio / Size | Wide / 24.1" viewable diagonal area |
| | Active Area / Pixel Pitch | 518.4(H) x 324.0(V) mm / 0.27(H) x 0.27(V) mm |
| | Native Resolution / Colors | 1920(H) x 1080(V) / 16.7M |
| | Brightness / Contrast | 300 cd/m2 (typ) / 1000 : 1 |
| | Response Time | ≤ 14ms (G-to-G) |
| | Viewing Angle (typical) | H:178o (- 89o ~ + 89o) , V: 178o (- 89o ~ + 89o) |
| | Light Source | LED backlight, Long life, 35,000 hrs (typ) |
| System | CPU | Intel® Core i3 / i5 / i7 Processors |
| | BIOS | UEFI |
| | System / Graphic Chipset | Intel® HD Graphics (By CPU); Shared Memory |
| | System Memory | 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB) |
| | HDD | 4 x SATA2 |
| | I/O port | 1 x VGA |
| | | 2 x USB |
| 1 x COM | | |
| 1 x LAN | | |
| Expansion | N / A | |
| Power | Power Input | 9-19V DC-In (4-pin ATX PWR Con) |
| | Power Consumption | 85Watt, <1 Watt |
| Operating Condition | Temperature / Humidity | 0o C ~ 50o C (32o F ~ 122o F) , 10% ~ 90% (no condensation) |
| Dimensions | Physical | Please refer to Drawing |
| | Carton | W x H x D = TBD |

| Options | Touch | Video / TV | Enhanced Panel | Others |
|---------|------------------|----------------------|--------------------------|------------------------------|
| | Resistive touch | SV + AV | Panel with LED backlight | Digital Signage(Stand alone) |
| | Capacitive touch | SV + AV + AV_Looping | High brightness panel | Networking Digital Signage |
| | SAW touch | SV + AV + TV | Wide Temperature | Motion Sensor |
| | Infrared touch | | Sunlight Readable | Light Sensor |
| | Protected glass | | | Auto-Dimming |



LCD OPTIONS



Optical Bonding Options

- Optical Bonding provides the best reduction of ambient light washout of any commercially available enhancement technology.
- Optical Bonding has a lower cost than most other competing technologies.
- Optical Bonding offers superior ruggedization, enhancing the display durability under vibration, shock and other environmental extremes.



RS-232 Remote Control Options

Remote Control Protocol: Command Code to set system



9-36V DC Input Options

iTech offers a selection of DC input from 9V to 36V



Light Sensor and Motion Sensor Options

iTech LCD offers Light and Motion Sensor

Privacy Filter

Front Glass Options:

- Anti Reflective AR Glass 3mm
- Anti Reflective AR Glass 6mm Vandal-Resistance
- Anti Reflective AR Glass 8mm Vandal-Resistance
- Anti Glare AG Glass 3mm

DRAWINGS:

