

Model: EMCW1540WT-i5

Panel PC IP65 Front 15.4" Wide LCD Monitor,
Intel® Core™ H61 i5-2390T Processor 3.5
GHz

Features:

- 15.4" LCD panel, 1280 x 800, 400 nits
- Intel® Core™ i5 Processor
- Intel® QM57
- 2 x DDR3 SO-DIMM Up to 8GB 800/1066 MHz SDRAM
- 1 x VGA, 1 x DVI, 6 x USB, 2 x COM, 2 x LAN
- 1 x PS2, Mic-in, Line-in, Line-out



Specification:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	wide / 15.4" viewable diagonal area
	Active Area / Pixel Pitch	331.56(H) x 207.23(V) mm / 0.25(H) x 0.25(V) mm
	Native Resolution / Color	1280(H) x 800(V) / 262 K
	Brignthess / Contrast	400 cd/m ² (typ) / 700 : 1
	Response Time	≤ 16 ms
	Viewing Angle (Typical)	H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)
	Light Source	LED, Long life, 35,000 hrs (typ)
System	CPU	Intel® Core™ i5 Processor; FSB 1066MHz
	BIOS	AMI
	System / Graphic Chipset	Intel® QM57 / HD Graphics Integrated
	System Memory	2 x DDR3 SO-DIMM Up to 8GB 800/1066 MHz SDRAM
	HDD	6 x SATA
	I/O Ports	1 x VGA, 1 x DVI
		6 x USB
		2 x COM
2 x LAN		
	1x(K/B and Mouse)	
	Mic-in, Line-in, Line-out	
Expension	1 x Mini PCI-e	
Power	Power Input	24V DC-IN (4-Din Connector)
	Power Consumption	68 Watt, <1 Watt
Environmental	Operating Temperature	-30°C~80°C (-22°F~176°F), 10%~90% (non condensation)
	Operating Humidity	0%~95%(non-condensing)

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	Wifi	Networking Digital Signage
	Capacitive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto Light Sensor
	Sunlight Readable		Auto-Dimming	

Mechanical Drawing:

