

All in One PANEL PC with Touch

All in one PC Industrial Chassis/Wall Mount Metal Housing , 20.1" LCD monitor, 1600 x 1200, 400 nits, Side OSD with Capacitive Touch and USB Controller Intel® Core™ i3-2100T Processor (3M Cache, 2.5 GHz, 2C/4T, 35W) installed, 4 GB Memory and 500GB HDD 3.5" SATA (Model: [EPC2010i3-TC](#))



Features:

- 20.1" LCD panel, 1600 x 1200, 400 nits
- Intel® Core™ i7/i5/i3/ Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out



Specification:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	4 : 3 / 20.1" viewable diagonal area
	Active Area / Pixel Pitch	408.0(H) x 306.0(V) mm / 0.255(H) x 0.255(V) mm
	Native Resolution / Color	1600(H) x 1200(V) / 16.7 Million
	Brighthness / Contrast	400 cd/m (typ) / 800 : 1
	Response Time	^ 8 ms(G-to-G)
	Viewing Angle (Typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)
	Light Source	LED, Long life, 35,000 hrs (typ)
System	CPU	Intel® Core™ i7/i5/i3/ Celeron Processor
	BIOS	UEFI
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
	HDD	4 x SATA2
	I/O Ports	1 x VGA
		2 x COM
		1 x HDMI
6 x USB(2.0)		
2 x LAN		
	Audio Line In	
Expension	1 x Mini PCI-E (Half Size)	
Power	Power Input Power	ATX PWR (24+4 pin)
	Consumption	80 Watt, <1 Watt
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)
	Operating Humidity	0%~95% (non-condensing)

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Mechanical Drawing:

