

# EPPMF Series: IP65 Panel Mount

IP65 Panel Mount (OSD front) 15" LCD monitor, 1024x768, LED 350 nits, WV(170°/170°), WT(-15°C~65°C), VGA input with Resistive touch screen

**Model: EPPMF1500WVWT-TR**



## FEATURES HIGHLIGHTS:

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV.SV.AV-Looping
- Complete custom design/solution for OEM customers
- IP65 front side sealed for water-dust proof

## SPECIFICATIONS:

|                            |  |  |  |
|----------------------------|--|--|--|
| <b>Panel</b>               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating         |  |
|                            | Aspect Ratio / Size  | 4 : 3 / 15" viewable diagonal area                         |  |
|                            | Active Area / Pixel Pitch  | 304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm          |  |
|                            | Native Resolution / Colors   | 1024(H) x 768(V) / 16.2 M                                  |  |
|                            | Brightness / Contrast  | 350 cd/m <sup>2</sup> (typ) / 1500 : 1                     |  |
|                            | Response Time  | < 35 ms  |  |
|                            | Viewing Angle (typical)  | H. 170o (- 85o ~ + 85o) , V. 170o(- 85o ~ + 85o)           |  |
|                            | Light Source   | LED backlight, Long life, 35,000 hrs (typ)                 |  |
| <b>Input Sources</b>       | PC System  | Signal   | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)          |
|                            |  | Sync   | Separate Sync, Composite Sync, Sync On Green             |
|                            |  | Frequency  | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 - 75Hz |
|                            | Audio System   | 2W speaker x 2   |  |
| <b>Input Terminals</b>     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |  |  |
| <b>Convenient Features</b> | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |  |  |
|                            | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |  |  |
| <b>Power</b>               | Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz              |  |  |
| <b>Power Consumption</b>   | Operation / Power Saving   | 20 watt , < 2 watt (Support DPMS)                          |  |
| <b>Operating Condition</b> | Temperature / Humidity   | -15°C ~ 65°C (5°F ~ 149°F) , 10% ~ 90% (no condensation)   |  |
| <b>Storage Condition</b>   | Temperature / Humidity   | -30°C ~ 80°C (-22°F ~ 176°F) , 10% ~ 90% (no condensation) |  |
| <b>Certification</b>       | FCC , CE   |  |  |
| <b>Dimensions</b>          | Physical   | Please refer to Drawing                                    |  |
|                            | Carton   | W x H x D = TBD  |  |
| <b>Weight</b>              | N.W. / G.W.  | 4 Kgs / 5 Kgs  |  |
| <b>Container Loaded</b>    | 20ft / 40ft / 40ft HQ  | TBD (Sets , By pallet)                                     |  |

|                |                  |                      |                          |                              |
|----------------|------------------|----------------------|--------------------------|------------------------------|
| <b>Options</b> | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|                | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|                | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|                | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|                | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|                | Protected glass  |                      |                          | Auto-Dimming                 |

**MECHANICAL DRAWING:**

