



# Model: EP1700-TR

## 17" Plastic Case LCD Monitor with Resistive Touchscreen

### Features:

- Elegant design with slim bezel
- Integrated amp and stereo speakers give you a complete multimedia experience
- Long lasting product cycle-enclosure controlled, future generation panels phased-in without external changes

### Specification:

<b>Panel</b>	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4 : 3 / 17" viewable diagonal area	
	Active Area / Pixel Pitch	337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm	
	Native Resolution / Colors	1280(H) x 1024(V) / 16.7 Million	
	Brightness / Contrast	300 cd/m <sup>2</sup> (typ) / 800 :1	
	Response Time	g 5 ms	
	Viewing Angle (typical)	H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°)	
	Light Source	CCFL , Long life, 50,000 hrs (typ)	
<b>Input Sources</b>	PC System	Signal	Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz
Audio System	2W speaker x 2		
<b>Input Terminals</b>	1 x VGA (15 Pin Female D-Sub), 1 x PC Audio (Stereo Headphone Jack), 1 x AC Outlet		
<b>Convenient Features</b>	Auto Calibration , Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)		
<b>Power</b>	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
<b>Power Consumption</b>	Operation / Power Saving	30 watt, < 2 watt (Support DPMS)	
<b>Operating Condition</b>	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation)	
<b>Storage Condition</b>	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F), 10% ~ 90% (no condensation)	
<b>Certification</b>	FCC,CE		
<b>Dimensions</b>	Physical	With Base(W x H x D): 374.5 x 366.7 x 183.0 mm	
		Without Base(W x H x D): 374.5 x 322.2 x 49.6 mm	
	Carton	W x H x D = 416 x425 x142 mm	
<b>Weight</b>	N.W. / G.W.	5.0 Kgs / 6.0 Kgs	
<b>Container Loaded</b>	20ft / 40ft / 40ft HQ	1040 / 2160 / NA (Sets , By pallet)	

<b>Options</b>	Enhanced Panel	Video / TV	Others
	Panel with LED backlight	DVI	Digital Signage(Stand alone)
	High brightness panel	HDMI	Motion Sensor
	Wide Temperature	SV + AV + TV	Light Sensor
	Sun Light Readable		Auto-Dimming

# Mechanical Drawing:

