



Model: EP1700HB-TR

17" Plastic Case LCD Monitor with Resistive Touchscreen

Features:

- Elegant design with slim bezel
- Integrated amp and stereo speakers give you a complete multimedia experience
- Long lasting product cycle-enclosure controlled, future generation panels phased-in without external changes

Specification:

| | | | |
|----------------------------|--|--|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Aspect Ratio / Size | 4 : 3 / 17" viewable diagonal area | |
| | Active Area / Pixel Pitch | 337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm | |
| | Native Resolution / Colors | 1280(H) x 1024(V) / 16.7 Million | |
| | Brightness / Contrast | 420 cd/m ² (typ) / 800 :1 | |
| | Response Time | g 5 ms | |
| | Viewing Angle (typical) | H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°) | |
| | Light Source | CCFL , Long life, 50,000 hrs (typ) | |
| Input Sources | PC System | Signal | Analog RGB (0.7/1.0 V _{p-p} , 75 ohms) |
| | | Sync | Separate Sync, Composite Sync, Sync On Green |
| | | Frequency | F _h : 30 - 82Khz , F _v : 50 -75Hz |
| | Audio System | 2W speaker x 2 | |
| Input Terminals | 1 x VGA (15 Pin Female D-Sub), 1 x PC Audio (Stereo Headphone Jack), 1 x AC Outlet | | |
| Convenient Features | Auto Calibration , Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B) | | |
| | OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm) | | |
| Power | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz | | |
| Power Consumption | Operation / Power Saving | 30 watt, < 2 watt (Support DPMS) | |
| Operating Condition | Temperature / Humidity | 0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation) | |
| Storage Condition | Temperature / Humidity | - 20°C ~ 60°C (- 4°F ~ 140°F), 10% ~ 90% (no condensation) | |
| Certification | FCC,CE | | |
| Dimensions | Physical | With Base(W x H x D): 374.5 x 366.7 x 183.0 mm | |
| | | Without Base(W x H x D): 374.5 x 322.2 x 49.6 mm | |
| | Carton | W x H x D = 416 x425 x142 mm | |
| Weight | N.W. / G.W. | 5.0 Kgs / 6.0 Kgs | |
| Container Loaded | 20ft / 40ft / 40ft HQ | 1040 / 2160 / NA (Sets , By pallet) | |

| | | | |
|----------------|--------------------------|--------------|------------------------------|
| Options | Enhanced Panel | Video / TV | Others |
| | Panel with LED backlight | DVI | Digital Signage(Stand alone) |
| | High brightness panel | HDMI | Motion Sensor |
| | Wide Temperature | SV + AV + TV | Light Sensor |
| | Sun Light Readable | | Auto-Dimming |

Mechanical Drawing:

