



# Model: EPC1700HB

## 17" Plastic Case LCD Monitor

### Features:

- Elegant design with slim bezel
- Integrated amp and stereo speakers give you a complete multimedia experience
- Long lasting product cycle-enclosure controlled, future generation panels phased-in without external changes

### Specification:

|                            |  |  |   |
|----------------------------|--|--|---|
| <b>Panel</b>               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating         |   |
|                            | Aspect Ratio / Size  | 4 : 3 / 17" viewable diagonal area                         |   |
|                            | Active Area / Pixel Pitch  | 337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm          |   |
|                            | Native Resolution / Colors   | 1280(H) x 1024(V) / 16.7 Million                           |   |
|                            | Brightness / Contrast  | 420 cd/m <sup>2</sup> (typ) / 800 :1                       |   |
|                            | Response Time  | g 5 ms   |   |
|                            | Viewing Angle (typical)  | H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°)           |   |
|                            | Light Source   | CCFL , Long life, 50,000 hrs (typ)                         |   |
| <b>Input Sources</b>       | PC System  | Signal   | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                            |  | Sync   | Separate Sync, Composite Sync, Sync On Green            |
|                            |  | Frequency  | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                            | Audio System   | 2W speaker x 2   |   |
| <b>Input Terminals</b>     | 1 x VGA (15 Pin Female D-Sub), 1 x PC Audio (Stereo Headphone Jack), 1 x AC Outlet |  |   |
| <b>Convenient Features</b> | Auto Calibration , Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B)          |  |   |
|                            | OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)                           |  |   |
| <b>Power</b>               | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz     |  |   |
| <b>Power Consumption</b>   | Operation / Power Saving   | 30 watt, < 2 watt (Support DPMS)                           |   |
| <b>Operating Condition</b> | Temperature / Humidity   | 0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation)     |   |
| <b>Storage Condition</b>   | Temperature / Humidity   | - 20°C ~ 60°C (- 4°F ~ 140°F), 10% ~ 90% (no condensation) |   |
| <b>Certification</b>       | FCC,CE   |  |   |
| <b>Dimensions</b>          | Physical   | With Base(W x H x D): 374.5 x 366.7 x 183.0 mm             |   |
|                            |  | Without Base(W x H x D): 374.5 x 322.2 x 49.6 mm           |   |
|                            | Carton   | W x H x D = 416 x425 x142 mm                               |   |
| <b>Weight</b>              | N.W. / G.W.  | 5.0 Kgs / 6.0 Kgs  |   |
| <b>Container Loaded</b>    | 20ft / 40ft / 40ft HQ  | 1040 / 2160 / NA (Sets , By pallet)                        |   |

|                |                          |              |                              |
|----------------|--------------------------|--------------|------------------------------|
| <b>Options</b> | Enhanced Panel           | Video / TV   | Others                       |
|                | Panel with LED backlight | DVI          | Digital Signage(Stand alone) |
|                | High brightness panel    | HDMI         | Motion Sensor                |
|                | Wide Temperature         | SV + AV + TV | Light Sensor                 |
|                | Sun Light Readable       |              | Auto-Dimming                 |

# Mechanical Drawing:

