

Sunlight Readable Chassis/Surface mount Highbrightness LCD

15" 1024 x768, 1000nits LED Sunlight Readable High Brightness Wide Temperature -30C to 85C Rugged Industrial Chassis/Surface mount LCD Monitor with VGA input. Power Consumption 11.4 Watts. Front OSD membrane with "Up" and "Down" to Control Brightness directly. Recommend to use LED BKU for 0-100% brightness.



Model: YCH1500WTHB-FOSD

Wide Temp: -30°C to 85°C

FEATURES:

- Front OSD membrane with "Up" and "Down" to Control Brightness directly. Recommend to use LED BKU for 0~100% brightness.
- Sunlight Readable.
- LED Backlight.
- 15.0" XGA TFT LCD with resolution up to 1024 x 768
- Suitable for military, tablet, ruggedized PC, kiosk, advertising, POS, marine, transportation, gaming, gas pump.

System Specifications

Brightness (cd/m ²)	1000
Display Resolution (pixel)	XGA(1024x768)
Display Color	262K / 16.2M
Viewing Angles (CR≥10)	80 / 80 / 70 / 60
Contrast Ratio	700:1
Response Time (msec)	8
Backlight Unit	LED

MECHANICAL DRAWINGS:

Unit:mm

