## SUNLIGHT READABLE CHASSIS MOUNT HIGH BRIGHTNESS

21.5" Industrial Chassis/Surface Mount Metal Housing High Brightness LCD 1920\*1080 300nits 1000:1 with VGA + DVI input

Model: YCHW2150E



## **FEATURES:**

- Sunlight Readable.
- 21.5" Full-HD TFT LCD with resolution up to 1920x1080.
- Suitable for military, tablet, ruggedized PC, kiosk, advertising, POS, marline, transportation, gaming, gas pump.

## **System Specifications**

1	
Screen Diagonal	21.5
Active Area	476.64 (H) x 268.11 (V)
Pixels H x V	1920(x3) x 1080
Pixel Pitch	0.24825 x 0. 24825
Pixel Arrangement	R.G.B. Vertical Stripe
Display Mode	VA Mode, Normally Black
Nominal Input Voltage (VDD)	+5.0 V
Typical Power Consumption	18.14 W (Cell 3.5W + LED 14.64W) (with LED driver board, all white pattern)
Weight	1,750 (± 175 g)
Physical Size	495.6(W) × 292.2(H) × 11.7(D)
Electrical Interface	Dual channel LVDS
Surface Treatment	Anti-glare, Hardness 3H
Support Color	16.7M colors (RGB 8 bits)
Temperature Range	
Operating	0~60°C
Storage (Non-Operating)	-20~60°C
RoHS Compliance	RoHS Compliance
Light Bar Unit	LED, Non-Replaceable



## **MECHANICAL DRAWING:**



