

Sunlight Readable Chassis High Brightness LCD

Industrial Chassis Metal Housing High Brightness

46" LCD 1500nits LED Backlight 1920 x 1080, Brightness
Backlight VGA + DVI input (Panel Enhancement to prevent isotropic blackout
under direct Sun up to 110C) Contrast Ratio 4000:1, 110V AC, Operating Temp 5F to 140F
(-15C to 60C) One(1) Year Return to Depot Warranty, Life time 60K hours, operating
Time 20 hours/Per day, Anti Shock 30G, Anti Vibration 1G (2-200Hz)



Model: YCHW4600HBWT

FEATURES:

- . High contrast color TFT-LCD Monitor support resolution up to 1920 x 1080.
- . Power management system conforms to VESA DPMS and EPA Energy Star standards.
- . Universal Power adapter.
- . Support DDC1 & DDC2B for Plug & Play compatibility.
- . Advanced OSD control for picture quality adjustment.
- . Detachable stand for wall-mounting adjustment.
- . Heavy duty monitor with steel frame.
- . Custom design by request.

SPECIFICATIONS:

Item	Specification
Panel Type	46.0-inch TFT LCD
Screen Diagonal	46.0-inch
Active Display Area (mm)	1018.08(H) x 572.67(V)
Pixel Pitch (um)	0.53(H) x 0.53(V)
Number of Pixels	1,920x1,080
Contrast Ratio	4000:1
Color Arrangement	R.G.B. Vertical Stripe
Brightness (cd/m ²)	1500 cd/m ²
Viewing Angle(Typ.)	89/89/89/89 (R/L/U/D)
Signal Connector	VGA+DVI-D
Power Source	AC100 ~ 240V, Universal +/- 10%
Power Management	VESA DPMS Compliant
Operating Temperature	-15°C to 60°C
Plug & Play	VESA DDC 1/2B

MECHANICAL DRAWINGS:

