

INDUSTRIAL OPEN FRAME METAL HOUSING HIGH BRIGHTNESS

10.4" LCD 800x600, -30~80C, 1500nits DVI input with 12V input (no external power adapter) with Optical Bonding + 5 Wire Resistive Touch Screen and USB Controller (eGalax drivers)+RS232 remote command control code



Model: YOP1040-TR-HP01

FEATURES:

- High Brightness.
- LED Backlight.
- 10.4" SVGA TFT LCD with resolution up to 800x600.
- Suitable for military, tablet, ruggedized PC, kiosk, advertising, POS, marine, transportation, aviation, gas pump.

SYSTEM SPECIFICATIONS

Active Display Area (mm)	211.2(H) x 158.4(V)
Display Resolution (pixel)	SVGA (800 x 600)
Pixel Pitch (mm)	0.264 x 0.264
Display Color	262K / 16.2M
Viewing Angles (CR≥10)	70/70/55/65 (R/L/U/D)
Contrast Ratio	500
Brightness (cd/m ²)	1500
Response Time (msec)	30
Backlight Unit	LED
Power Source	AC 100~240V, Universal
Signal Connector	DVI
Optional Touch Screen	Resistive
Temperature	-30°C ~ 80°C
Touch	5 Wire Resistive

MECHANICAL DRAWINGS:

