

Sunlight Readable Open Frame High Brightness LCD

Industrial Open Frame Metal Housing High Brightness

32" LCD 1920*1080, contrast 1000:1 with VGA input 1500nits LED Backlight Contrast Ratio 3000:1110/220V AC, Operating Temp -4F to 140F (-20C to 60C) One(1) Year Return to Depot Warranty, Life time 60K hours, operating Time 24 hours/Per day (Moving Pictures) Anti Shock 30G, Anti Vibration 1G (2-200Hz), (Panel Enhancement to prevent isotropic blackout under direct Sun up to 85C)



Model:YOPW3200HB2WT

1500nits



FEATURES:

- . High contrast color TFT-LCD Monitor support resolution up to 1920 x 1080.
- . Power management system conforms to VESA DPMS and EPA Energy Star standards.
- . Universal Power adapter.
- . Support DDC1 & DDC2B for Plug & Play compatibility.
- . Advanced OSD control for picture quality adjustment.
- . Detachable stand for wall-mounting adjustment.
- . Heavy duty monitor with steel frame.
- . Custom design by request.

SPECIFICATIONS:

Item	Specification
Panel Type	32.0-inch TFT LCD
Screen Diagonal	32.0-inch
Active Display Area (mm)	698.4 (H) x 392.85(V)
Pixel Pitch (um)	0.3637 (H) x 0.3637 (W)
Number of Pixels	1,920x1,080
Contrast Ratio	3000:1
Color Arrangement	R.G.B. Vertical Stripe
Brightness (cd/m ²)	1500 cd/m ²
Viewing Angle(Typ.)	89/89/89/89 (R/L/U/D)
Signal Connector	VGA Input
Power Source	AC110 ~ 220V, Universal +/- 10%
Power Management	VESA DPMS Compliant
Operating Temperature	-20°C to 60°C
Plug & Play	VESA DDC 1/2B

MECHANICAL DRAWINGS:

