

Sunlight Readable Panel Mount High Brightness LCD

Industrial LCD Monitor with Aluminum Front Bezel

21.5" (16:9) True Flat Bezel PCAP Touch Monitor / 1920x1080 / 1500nits / Front 10mm Aluminum bezel / Front IP66 / VGA+DVI+HDMI input / Panel Mount / VESA Mount / DC 12V input / PCAP Touch (6mm Cover glass) with USB controller (10 points in Windows7/10)

1500nits



Model: YPMW2150HB-TPCT

FEATURES:

- Sunlight Readable.
- Color Active Matrix Liquid Crystal Display.
- FULL HD (1920 x 1080)
- Suitable for military, tablet, ruggedized PC, kiosk, advertising, POS, marine, transportation, gaming, gas pump.

System Specifications

Panel Type	21.5-inch TFT LCD
Screen Diagonal	21.5-inch
Active Display Area (mm)	476.64 (H) x 268.11 (V)
Pixel Pitch (um)	248.25 x 248.25
Number of Pixels	1920 x 1080
Contrast Ratio	1000: 1
Color Arrangement	R.G.B. Vertical Stripe
Brightness (cd/m ²)	1500 cd/m ²
Viewing Angle(Typ.)	178/178 (H/V)
Signal Connector	VGA+DVI+HDMI
Power Input	DC 12V
Power Consumption	62W Typical, normal operation
Power Management	VESA DPMS Compliant
Operating Temperature	-20 ~ 65°C Surface Temp up to 110°C
Storage Temperature	-20 ~ 60°C

MECHANICAL DRAWINGS:

