

YK3000P

Rackdrawer Keyboard with Pointing Device

Ruggedized rackdrawer keyboards from iTechLCD corner the market on rackmount peripherals. The YK3000P offers the benefit of an integrated ruggedized HulaPoint™ pointing device. Standard size units have 14-inch rails (15-inch-deep drawer) and come with chrome handle or pull slot options. Larger size units have 16-inch rails (17-inch drawer) and come with T-handle or locking T-handle options. The drawers have a CRS steel construction, which is coated with black epoxy paint, and chrome-plated, ball-bearing slides.



Technical Specifications

Certifications	NEMA 12 UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	KEYBOARD: 5V@ 10 ma (from CPU port) HULAPOINT: 5V@ 10 ma (from mouse conn. port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C
Weight	16 lbs (7.36 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	Pull Slot/Chrome Handle: 19" x 15" x 1U (1.75") (w-h-d) 482.6mm x 381mm x 44.5mm T-handle: 19" x 17" x 1U (1.75") 482.6mm x 431.8mm x 44.5mm

Model Numbers

Features and Benefits

- Integrated HulaPoint Pointing Device
- Slide Load Rating: 130 Lbs/Pair
- USB, PS/2 and AT/serial configurations available



Distributed by:

i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com

