

FANLESS Water Proof Touch Panel PC

15" (4:3) resistive Touch Screen Fanless Panel PC

Intel i3 3217U CPU(1.8G) ,Front Panel Water Resistant, 0°C ~ 45° C
Operating temperature, 4G RAM,320GB HDD, 2xGiga LAN ports, PC
power input, black brazel for panel Mount, 2xCOM standard
(option more COM), 4xUSB

MODEL: MPC1500-i3



FEATURES:

- 15" (4:3) LED backlight Industrial Panel PC
- Intel® Core i3-3217U Processor
- One SO- DDR3 1333 DIMM slot , Support Max. 10G
- 5-wire resistive type touch screen supported
- 1*SATA for 2.5"HDD , 1* mSATA for SSD
- 2COM(6 COM Option) + 4USB + 1*VGA + 2*Giga LAN
- 1* HDMI + 1 x mPCIe space
- WIFI 802.11 b/g/n (option)
- 1x Internal USB2.0 for Keypro
- OS support: Win7(e), Win XP(e), Win CE, Linux



SPECIFICATIONS

LCD Specs

Size	15"
Resolution	1024 (W) x 768 (H)
Brightness (cd/m ²)	400 cd/m ²
Contrast Ratio	700:1
LCD color	262K / 16.2M
Pixel Pitch (mm)	0.297(H) x 0.297(V)
Viewing Angle (H-V)	160° (H) / 140° (V)
Backlight MTBF	50000 hrs (LED backlight)

TOUCH

Touch Screen	5-wire resistive type with USB Interface (PCAP Option)
Touch Controller	EETI Touch kit

SYSTEM

CPU	Intel® Core™ i3-3217U CPU	
Chipset	Intel® NM70	
RAM	RAM 2G on Board, Support one 1333 MHz SO-DDR3 DIMM slot (max. 10GB)	
Ethernet	2*Realtek RTI.8111F PCIe GbE controller supporting ASF 2.0	
Audio Codec	Realtek ALC662 HD audio codec	
SSD	mSATA	
Input / Output	2 x RS-232 COM(6 COM Option) Port (DB-9) 2 x GbE LAN (RJ-45) 4 x USB2.0 1 x Audio jack 1 x MIC jack 1 x VGA + 1 x HDMI	1 x Power On button 1 x DC input jack 1 x DC input bypass terminal (Option) 1 x internal USB2.0 for Keypro
Expansion Interface	1x mPCIe slot	
System Cooling	CPU Heatsink Fan Cooling	

CONNECTIVITY

Wireless	IEEE 802, 11b/g/n(Option)
Bluetooth	Optional

PHYSICAL

Construction Front Panel	Optional Steel front frame and whole case
Mounting	Panel,Stand, and VESA 100mm x 100mm, 75mmx75mm
Color	Black
Dimensions (WxHxD)mm	363.4 x 285 x 87.8
Weight (N/G) Operation	5.0 kg

ENVIRONMENT

Operating Temperature (°C)	0 °C ~ 40°C
Storage Temperature (°C)	-20°C ~ 60°C
Humidity	10% to 95% (non-condensing)

POWER

Power Supply	60W power adapter Input: 90VAC~264VAC, 50/60 Hz, Output: 12VDC
Power Requirement	12 VDC
Power Consumption	

CERTIFICATION

IP Level	Front Panel IP 64
Safety & EMC	CE / FCC

MECHANICAL DRAWINGS

