

FANLESS Water Proof Touch Panel PC

17" (4:3) Resistive Touch Screen Fanless Panel PC

Intel i5 3317U CPU(1.7G ~2.6G) ,Front Panel Water Resistant, 0°C ~ 45° C
Operating temperature, 4G RAM,320GB HDD, 2xGiga LAN ports, PC
power input, black brazel for panel Mount, 2xCOM standard
(option more COM), 4xUSB

MODEL: MPC1700-i5



FEATURES:

- 17" (4:3) LED backlight Industrial Panel PC
- Intel Core i5-3317U CPU
- One SO- DDR3 1333 DIMM slot , Support Max. 8G
- 5-wire resistive type touch screen supported
- 1*SATA for 2.5"HDD , 1* mSATA for SSD
- 2COM(6 COM Option) + 4USB + 1*VGA + 2*Giga LAN
- 1* HDMI + 1 x mPCIe space
- WIFI 802.11 b/g/n (option)
- 1x Internal USB2.0 for Keypro
- OS support: Win7(e), Win XP(e), Win CE, Linux



SPECIFICATIONS

LCD Specs

Size	17"
Resolution	1280 (W) x 1024 (H)
Brightness (cd/m ²)	350 cd/m ²
Contrast Ratio	1000:1
LCD color	262K / 16.2M
Pixel Pitch (mm)	0.240(H) x 0.240(V)
Viewing Angle (H-V)	170° (H) / 165° (V)
Backlight MTBF	50000 hrs (LED backlight)

TOUCH

Touch Screen	5-wire resistive type with USB Interface (PCAP Option)
Touch Controller	EETI Touch kit

SYSTEM

CPU	Intel® Core™ i5-3317U CPU	
Chipset	Intel® NM70	
RAM	Support one 1333 MHz SO-DDR3 DIMM slot (max. 8GB)	
Ethernet	2*Realtek RTI.8111F PCIe GbE controller supporting ASF 2.0	
Audio Codec	Realtek ALC662 HD audio codec	
SSD	mSATA	
Input / Output	2 x RS-232 COM(6 COM Option) Port (DB-9) 2 x GbE LAN (RJ-45) 4 x USB2.0 1 x Audio jack 1 x MIC jack 1 x VGA + 1 x HDMI	1 x Power On button 1 x DC input jack 1 x DC input bypass terminal (Option) 1 x internal USB2.0 for Keypro
Expansion Interface	1x mPCIe slot	
System Cooling	CPU Heatsink Fan Cooling	

CONNECTIVITY

Wireless	IEEE 802, 11b/g/n(Option)
Bluetooth	Optional

PHYSICAL

Construction Front Panel	Optional Steel front frame and whole case
Mounting	Panel,Stand, and VESA 100mm x 100mm, 75mmx75mm
Color	Black
Dimensions (WxHxD)mm	399.4 x335 x 87.8
Weight (N/G) Operation	5.8 kg

ENVIRONMENT

Operating Temperature (°C)	0 °C ~ 40°C
Storage Temperature (°C)	-20°C ~ 60°C
Humidity	10% to 95% (non-condensing)

POWER

Power Supply	60W power adapter Input: 90VAC~264VAC, 50/60 Hz, Output: 12VDC
Power Requirement	12 VDC
Power Consumption	

CERTIFICATION

IP Level	Front Panel IP 64
Safety & EMC	CE / FCC

MECHANICAL DRAWINGS

