

Fanless PANEL PC

Fanless Panel PC 10.4" Atom N270 1.6GHz 945GSE 2GB (Max2GB) 2.5" 320GB 2 GigaLAN 4 COM2 @ 422/485 60W Adapter XP Pro 250 cd/m2

Model: BBC1040



Features:

- Fanless
- Intel Atom N270 1.6GHz Processor, FSB 533MHz
- 10.4" High brightness TFT-LCD with resolution of 800x600
- DC 11~32V Wide-Range Power Input
- One 200 Pin SO-DIMM socket, up to 2GB DDR2 533 MHz SDRAM
- Sealed Resistive Touchscreen



Specifications

Processor System	Intel® Atom™ N270 1.6 GHz built-in, FSB 533 MHz
Memory	1 x 200 Pin SO-DIMM socket, support up to 2 GB DDR2 SDRAM 533 MHz default 1GB
System Chipset	Intel® 945GSE+ ICH7M
External I/O Port	<ul style="list-style-type: none">• 4 x USB ports• 2 X RJ-45 ports (GbE)• 1 x DB-9 RS232 (COM 1)• 2 x DB-9 (COM2/COM3) RS232 by cables, COM2 (RS232/422/485 selection, default RS232), COM3 (RS232)• 1 x VGA port• 1 x Audio, Line-out• 1 x 3 Pin DC Power input terminal block
Storage	1 x 2.5" SATA HDD 1 x external CF slot
Expansion Slots	None
OS Support	Windows® CE 5.0, XP Pro, XP Embedded, Windows® 7



LCD

Display Type Max.	10.4" TFT-LCD
Resolution Max.	800x600
Color	262K
Luminance (cd/m ²)	250
View Angle	H:130° / V:110°
Backlight Lifetime	30,000hrs

Touchscreen

Type	Overlay Resistive Touch
Light Transmission	80%

Power Supply

Power Input	DC 11~32V
-------------	-----------

Mechanical

Construction	Plastic molding front panel and metal housing
Color	Black
IP Rating	Front Panel IP 65 Compliance
Mounting	Panel / VESA 75x75 Mount
Dimension	317(W)x243(H)x75.7(D)mm
New Weight	3kgs

Environmental

Operating	0-50 °C
Storage Temperature	-20-60 °C
Storage Humidity	10-90% @40 °C non-condensing
Certificate	CE/FCC Class A Compliance



Mechanical Drawings

Unit : mm

