

I-Star, Power up your future.....

Performance, Powerful, Professional

Features

MODEL NO: D-200 Storm Series

- *19" 2U High-End Rackmount Chassis compliant to EIA RS-310C Standard
- *Detachable card cage for easy installation and maintenance
- *System environmental monitor (optional)
- *Changeable Filter at front bezel
- *Dual lockable latch doors
- *Different Color Bezel: RED/Silver/Blue/Golden/Black or OEM your own Color on Bezel.
- *DVR Back-plate (optional)
- *FCC/CE industrial Class A approval

Specifications

- *Chassis : Meet EIA RS-310C 19" 2U high, Aluminum Bezel and handle Rackmount standard; heavy-duty steel. SECC 1.2t (Japan)
- *Drive Space: 2x5.25" 2x3.5"
- *M/B size : 12x10 M/B
- *Riser Card: [3 x PCI Slots](#) (Standard)
1 x AGP + 2 x PCI Slots (Optional)
- *Front Panel: Power on/off, reset switch and USB 2.0; power and HDD active LED
- *Thermal Solution: 1x80mm
Ball bearing cooling fans; system environmental monitor (optional) and changeable air filter.
- *Altitude: 15,000 feet
- *Power Supply : I-Star 2U power / 2U Redundant Power
Mini Redundant Power
- *Temperature: 0~50C (operating);0~70C (Storage)
- *Humidity:5~95%; non-condensing
- *Safety Standard: FCC/CE on chassis and
FCC/CE/UL/TUV on power supply.
- *Dimensions/Weight: 19.0" W x 20.8"D x 3.5" H

Patent No.

- TW :200281 (for front panel structure)
- CM :ZL 01 2 59648.5
- TW :190240 (for long card holder)



Ordering Guide

- *D-200 Storm Series
19" 2U High , Full size Rackmount chassis (Black Color)
- *TC-2U/xx — I-Star 350w / 400w / 460w
- *TC-xxxR2U —I-Star 2U Redundant 2x350w / 2x400w

Photo of Chassis

