



1U 17" LCD KVM CONSOLE

Model: RCK1417

FEATURES:

- Monitor and compact keyboard with trackball or touchpad in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable iTechLCD covering.



Display Specifications:

Display Type: Active matrix TFT LCD	Resolution: 640 x 350
Colors Displayed: 16.7 million colors.	640 x 480
Contrast Ratio: 1000:1 typ.	800 x 600
Brightness: 280 cd/m2 typ.	1024 x 768
Viewing Angle: Horizontal: 170° Vertical: 160°	1280 x 1024
Response Time: 25ms Typ.	Display Area: 17" Diagonal.
	Horizontal Frequency: 31.5 to 80 KHz
	Vertical Frequency: 56 to 75 Hz.

General Specifications:

Dimensions: 19.0" (W) x 1.75" (H) x 20.80" (D)
Weight: 25 lbs
Power (TFT Display): 90 - 260 VAC, 50/60 Hz. 60 Watts maximum
On-Screen Controls: Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values
Plug & Play: DDC1 and DDC2B
Temperature: Operating: 0° C to 50° C Storage: -20° C to 60° C
Humidity: Operating: 10 to 85% RH (max)
Input Signal (VGA): R.G.B. analog video, TTL H & V sync
Input Connector: Display: 15-pin mini D-Shell
Colors Available: Black

Keyboard and Mouse Specification:

Rollover: Alpha N-key rollover.
Auto repeat: Yes.
Self Diagnostics: At power on and system reset.
Data Buffer: All codes buffered before sending.
Operating voltage: +5 VDC +/- 5%.
Operating current: 100 mA max.
Trackball Size: 16mm.
Touchpad Size: 2.1" X 1.25"
Buttons: Left and Right, Scroll(touchpad)
Interface: Keyboard: PS/2 or USB(U). Trackball: PS/2 or USB(U). Touchpad: PS/2 or USB(U).
Compatibility: Windows operating systems.

