

Rackmount Keyboard Drawer

1U Rackmount Compact 17" TFT LCD Monitor
with cherry keyboard and two button touchpad in
1U of Rack Space

Model: RCK1617



FEATURES

- Monitor and Cherry™ keyboard with two button touchpad in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable covering.

SPECIFICATIONS:

| DISPLAY SPECIFICATIONS | |
|----------------------------|------------------------------|
| Display Type: | Resolution: |
| Active matrix TFT LCD | 640 x 350 |
| Colors: | 640 x 480 |
| 16.7 million colors | 800 x 600 |
| Contrast Ratio: | 1024 x 768 |
| 1000:1 typ. | 1280 x 1024 |
| Brightness: | Display Area: |
| 250 cd/m ² typ. | 17" Diagonal |
| Viewing Angle: | Horizontal Frequency: |
| Horizontal: 170° | 31.5 to 80 KHz |
| Vertical: 160° | Vertical Frequency: |
| Response Time: | 56 to 75 Hz. |
| 5ms. | |

| KEYBOARD AND TOUCHPAD SPECIFICATIONS | |
|--------------------------------------|--|
| Rollover: | Alpha N-key rollover. |
| Auto repeat: | Yes. |
| Self Diagnostics: | At power on and system reset. |
| Data Buffer: | All codes buffered before sending. |
| Operating voltage: | +5 VDC +/- 5%. |
| Operating current: | 200 mA. |
| Touchpad Size: | 2.2" X 1.6" |
| Buttons: | Left and Right. |
| Interface: | Keyboard: PS/2 or USB(U). Touchpad: PS/2 or USB(U). |
| Compatibility: | Windows operating systems. |

| GENERAL SPECIFICATIONS | |
|---|--|
| Dimensions: | |
| 19.0" (W) x 1.75" (H) x 25.75" (D) | |
| Weight: | |
| 27 lbs | |
| Power (TFT Display): | |
| 90 - 260 VAC, 50/60 Hz. | |
| 60 Watts maximum | |
| On-Screen Controls: | |
| Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values | |
| Plug & Play: | |
| DDC1 and DDC2B | |
| Temperature: | |
| Operating: 0°C to 50°C | |
| Storage: -20°C to 60°C | |
| Humidity: | |
| Operating: 10 to 85% RH (max) | |
| Input Signal (VGA): | |
| R.G.B. analog video, TTL H & V sync. | |
| Input Connector: | |
| Display: 15-pin mini D-Shell | |
| Colors Available: | |
| Black. | |