




VODPC3000

Fanless Rain Resistant Dust Resistant


Fanless and ventless, the iceman excels in harsh environments where others fail. Engineered to be dust, rain and splash resistant, the iceman is suitable for both indoor and outdoor locations. With the adapting Iceman IP65 extension box, all 6 faces are IP65-protected from dust and water penetration. The iceman fulfills all your media needs through integrated hardware MPEG-2 decoding acceleration. From Digital Signage to industrial computing, the deployment possibilities of iceman are endless.

Features

- Rain and Splash RESISTANT
- VIA UniChrome Pro AGP Graphics with MPEG-2 decoding acceleration
- Optional Wireless LAN 802.11b/g
- 1 x COM, 4 x USB 2.0
- VIA Vinyl 6 Channel Audio
- Totally FANLESS
- Wall Mountable



Dust Resistant



Rain Resistant



Splash Resistant Skirt



Specification

Processor : Onboard VIA C7 1 GHz/ Eden ULV 1.5 GHz
Memory : 512MB DDR2 memory supporting up to 1Gb
Graphics : VIA UniChrome Pro AGP graphics with MPEG-2 decoding acceleration (up to 1600 * 1200)

Maximum Resolution: 1920 X 1080
Network : 10 / 100 Ethernet, optional Wireless LAN 802.11b/g
Storage : 40GB IDE HDD
Audio : 1 x VGA, TV-Out (S-Video & RCA) (Dual View)
Video : 1 x VGA, TV-Out (S-Video & RCA) (Dual View)
IO : 2 x PS/2 ports, 1 x COM port, 4 x USB 2.0 ports

System Management : Wake-on-LAN, Watch Dog Timer, Keyboard / Timer Power-On, ACPI support, Power Failure Recovery

Operating Systems: Linux based operating systems
Microsoft Windows 2000 / XP / XPe
Microsoft Windows CE.NET 4.1 / 4.2 / 5.0

Power Input : DC 12V
Thermal System : Totally Fanless
Chassis : Totally Ventless: Dust, Rain and Splash Resistant

Temperature : 0 ~ 45°C (Operating), -20 ~ 70°C (Storage)

Dimensions : 8.03" (204mm) (H) x 7.99" (203mm) (W) x 2.44" (62mm) (D)

Net Weight: 2.4kg

Options

- Wireless LAN kit
- IP65 extension box (for I/O face)

